



AVAILABLE THROUGH
GRAINGER
||| FOR THE ONES WHO GET IT DONE



1 SAWHORSE IN CARRY POSITION



2 FOLD OUT THE 1ST SET OF LEGS




3 STRAIGHTEN THE CROSS BRACE



4 FOLD OUT THE 2ND SET OF LEGS



5 STRAIGHTEN THE CROSS BRACE



6 FOLD OUT THE WOOD SUPPORT PEGS

WARNING! TO REDUCE THE RISK OF PERSONAL INJURY, READ AND UNDERSTAND THE INSTRUCTIONS. SAWHORSE LEGS MUST BE FULLY OPEN WITH THE CROSS BRACE LOCKED DOWN. DO NOT STAND ON SAWHORSE. DO NOT OVERLOAD. MAXIMUM CAPACITY 800LBS. USE ONLY ON A FLAT, DRY, HARD AND LEVEL SURFACE.



NOTE: FOR YOUR SAFETY, PLEASE ENSURE YOU READ THESE INSTRUCTIONS CAREFULLY BEFORE USE, AND KEEP THESE INSTRUCTIONS IN THE WORK SPACE WHERE THE SAWHORSE WILL BE USED.

SAFE OPERATION AND USE OF THIS SAWHORSE

- 1** When lifting the sawhorse use proper lifting techniques to avoid personal injury.
- 2** Ensure work area is well lit while working.
- 3** Ensure saw horse is standing on a level surface that is clear, dry and free of debris.
- 4** Ensure all 4 legs have solid contact with the floor. If the saw horse is not positioned level and straight, loads placed upon it could fall, potentially causing damage to the item(s) loaded on it, and possible severe personal injury or death.
- 5** Ensure the load placed on any sawhorse does not exceed the applicable Safe Working Load Rating. Overloading can lead to failure of the sawhorse, potentially causing damage to the item(s) loaded on it, and possible severe personal injury or death.
- 6** Never stack sawhorses to obtain extra height.

Caution:

Do not apply weight in excess of 800 lbs (363kg) of uniformly distributed load on Sawhorse.
Do not use as a step ladder or standing platform.

Uniformly-Distributed Load

The maximum uniformly distributed load across the top rail of the saw horse, PER EACH SAW HORSE:

This means that the maximum weight that can be applied to this saw horse, per lineal foot, as is stated on the Retail Sticker and the instructions. "Uniformly-Distributed Load" means when all the weight is distributed evenly on the top rail. The amount of weight that can be applied to 2 identical saw horses is double this value. For example, a pallet or skid weighing not more than two times the Safe Working Load Rating can safely be carried by 2 of these saw horses.

LIFETIME | LIMITED WARRANTY



JS PRODUCTS, INC. | 6445 MONTESSOURI STREET | LAS VEGAS, NV 89113
800.255.7011 | FAX: 775.898.8773 | FOR MORE PRODUCTS AND ACCESSORIES GO TO WWW.PROTOCOLEQUIPMENT.COM