

## ARMEX® CLEANING AND COATING REMOVAL SYSTEMS

| Heavy Coating Removal | Application                                           | Formula                               | Micron Size | Flow Aid | Value Plus                |
|-----------------------|-------------------------------------------------------|---------------------------------------|-------------|----------|---------------------------|
|                       | General Purpose                                       | Maintenance XL                        | 270         | 2        | Value-priced              |
|                       | Surface preparation for new coating                   | Maintenance XL                        | 270         | 2        | Rinse Accelerator         |
|                       | High humidity or poor quality air supply              | Flow XL                               | 270         | 8        | Advanced Moisture Control |
|                       | Hard surface, rust removal or anchor pattern required | Profile XL – up to 1.5-2.0 mils       | 270         | 2        | 10% aluminum oxide, #70   |
| Light Coating Removal | Hard surface, rust removal or anchor pattern required | Profile XL 2+ up to 2-4 mils on steel | 270         | 2        | 20% aluminum oxide, #36   |
|                       | General Purpose                                       | Maintenance                           | 170         | 2        | Value-priced              |
|                       | Surface prep for new coating                          | Maintenance with Supracleen           | 170         | 2        | Rinse Accelerator         |
|                       | High humidity or poor quality air supply              | Flow M                                | 170         | 8        | Advanced Moisture Control |

| Specialty Formulas | Application                                                                                            | Formula                                 | Micron Size | Flow Aid | Value Plus                               |
|--------------------|--------------------------------------------------------------------------------------------------------|-----------------------------------------|-------------|----------|------------------------------------------|
|                    | Cleaning grease and oil removal for wet blasting                                                       | Hydroflex® XL                           | 270         | 2        | Surfactant                               |
|                    | Coatings removal or cleaning of soft substrates and composite materials                                | Composite                               | 70          | 8        | Advanced Moisture Control foil-lined bag |
|                    | Cleaning or preparation of electronic components or medical devices. Excellent as prep for adhesion    | Electronics                             | 70          | 8        | Advanced Moisture -35 lb Plastic Pail    |
|                    | Cleaning and ink removal on anilox printing rolls                                                      | Anilox Roll Cleaning                    | 70          | 8        | Advanced Moisture Control foil-lined bag |
|                    | Coatings removal on metals (aluminum) leaving a brushed surface. Use for heavy carbon deposit removal. | Turbine Formula – up to 5 mils on steel | 70          | 2        | 10% aluminum oxide, #220                 |