



DS222-18V

#10B0002N GRAINGER #830H26



SPECIFICATIONS

RPM	0-1600, 0-2500
Torque	70 In-lbs
Voltage	18V
Weight w/ 4.0Ah Battery	5.65
Height	9.59"
Length	13.66"
Width	3.36"
Drives Per Charge	Up to 2500*
Warranty	5 Year Limited

*When driving #6 x 1 1/4" screws through drywall into wood

FASTENERS

Screw Lengths	1" - 2"***
Screw Diameters	#6 - #12
Drive Type	#2 Phillips, #2 Square, REX

***1/2" - 2" with nosepiece sold separately, part #FC0822

INCLUDES

(2) Drive Bits
EA0297, EA0298



4.0Ah Li-Ion
Extended Life Battery

Charger

Storage Bag

2" 18V LI-ION 2500 RPM AUTO-FEED SCREWDRIVER

Powered by an efficient brushless motor, this high torque auto-feed screw gun includes an extended life 4.0Ah battery and a variable speed selector for heavy steel, a quick release feed system with our patented corner fit technology. The DS222-18V also features feed on return - the next screw is aligned with the bit for better line of sight and easier, more accurate screw placement.

TOOL OVERVIEW

- Patented corner-fit feed system
- Detachable feed system to expose bit for quick reversing
- Selectable 2500/1600 RPM high torque brushless motor
- Precise depth of drive adjustment with depth lock
- Quick slide button bit change
- 4.0Ah Li-Ion extended life battery included
- Quick charge battery charger
- Tool-free screw length adjustment
- Variable speed trigger with lock and reverse
- Adjustable belt hook

APPLICATIONS

High torque applications including metal framing/decking, crating, and gypsum/sheathing to heavy steel.



2500
RPM/TPM

**BRUSHLESS
MOTOR**

5
YEAR
LIMITED
WARRANTY

2" 18V LI-ION 2500 RPM AUTO-FEED SCREWDRIVER



#10B0002N

DS222-18V

- | | | |
|--|--|--|
| 1 CORNER-FIT FEED SYSTEM
Improved line of sight and better corner access | 5 SPEED SELECTION BUTTON (1600 RPM)
Quickly decrease the maximum speed for heavy steel applications | 9 1"-2" TOOL FREE ADJUSTABLE NOSE PIECE
Single nosepiece for wood and drywall applications with easy to read length markings |
| 2 FEED ON RETURN
Screws are in place before you drive for faster and more consistent performance | 6 ADJUSTABLE DEPTH-OF-DRIVE WITH DEPTH LOCK
For consistent flush drive or countersink (knob is on the reverse side, not shown) | 10 QUICK TOGGLE REVERSE SWITCH
Easily switch between forward and reverse |
| 3 REMOVABLE FEED SYSTEM
Detachable feed system for easier reversing | 7 EXTENDED LIFE 4.0AH LI-ION BATTERY
Uses latest cell technology for increased power and capacity | 11 VARIABLE SPEED TRIGGER
Change RPMs for self-tapping screws into steel |
| 4 HIGH TORQUE BRUSHLESS MOTOR
Provides increased performance and battery life with reduced size | 8 QUICK SLIDE BIT RELEASE
Easily insert or remove bits | 12 PATENTED SCREW GUIDE
Prevents screw binding for consistent feeding |

Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on SENCO fastening systems and how SENCO will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: www.Senco.com.



DS230 SERIES

#10B0002N GRAINGER #830H26
 #9Z0011N GRAINGER #60RJ87
 #9Z0012N GRAINGER #60RJ88
 #9Z0021N GRAINGER #60RJ89

SPECIFICATIONS

Weight	1.3 lbs
Height	5.53"
Length (vary by model)	10.34"-11"
Width	2.47"
Warranty	5 Year Limited

FASTENERS

Screw Lengths	1" - 2"
Screw Diameters	#6 - #12
Drive Type	#2 Phillips, #2 Square, REX

*1/2" - 2" with nosepiece sold separately,
 part #FC0822

COMPATIBILITY

DS230-S1 (9Z0001N) for SENCO

SG2510	SG4100
--------	--------

DS230-M1 (9Z0021N) for Makita

FS2200	XSF03
FS2500	XSF04
FS4200	XSF05
FS6200	

DS230-D1 (9Z0011N) for DeWalt

DW252	DW266
DW253	DW272
DW255	DW276
DW257	

DS230-D2 (9Z0012N) for DeWalt

DCF620	DCF630
--------	--------

INCLUDES

(2) Drive Bits
 EA0300, EA0301



Adaptor For DS230-D1*

* Not needed for other models



SENCO®
 SELECT MODELS



MAKITA®
 SELECT MODELS



DeWALT®
 SELECT MODELS



DeWALT®
 SELECT MODELS

2" AUTO-FEED SCREWDRIVER ATTACHMENTS

Convert a standard screwdriver into an auto-feed screw system in seconds.

TOOL OVERVIEW

- Patented corner-fit feed system
- Feed on return functionality to improve speed and reliability of drives
- Universal nosepiece for drywall and wood applications
- Easily remove attachment to access bit
- Tool-free screw length adjustment
- Supports several screwdriver models
- Precise depth of drive adjustment with depth lock
- Light weight and compact

APPLICATIONS

Ideal for drywall (into wood or steel studs), metal framing, sheathing, cement board



Screwdriver
 not included

2" AUTO-FEED ATTACHMENT



DS230 SERIES

- 1 CORNER-FIT FEED SYSTEM**
Improved line of sight and better corner access
- 2 FEED ON RETURN**
Screws are in place before you drive for faster and more consistent performance
- 3 REMOVABLE FEED SYSTEM**
Detachable feed system for easier reversing
- 4 1"-2" TOOL FREE ADJUSTABLE NOSE PIECE**
Single nosepiece for wood and drywall applications, with easy-to-read length markings
- 5 ADJUSTABLE DEPTH-OF-DRIVE WITH DEPTH LOCK**
For consistent flush drive or countersink (knob is on reverse side of attachment, not shown)
- 6 METAL FRAME**
For unmatched durability
- 7 SCREW GUIDE**
Prevents screw binding ensuring consistent feeding



DS530 SERIES

#10X0002N | #10X0012N | #10X0022N
GRAINGER #793G46 | #793G47

SPECIFICATIONS

Weight	3.4 lbs. (1.5 kg)
Height	3.5" (89 mm)
Length	33" (838 mm)
Width	2.75" (70 mm)
Warranty	5 Year Limited

FASTENERS

Screw Lengths	1" - 3"
Screw Diameters	#6 - #12
Drive Type	#2 Phillips, #2 Square, REX

*½" - 1" with nosepiece sold separately,
part #FC0887

COMPATIBILITY

DS530-S1 (10X0002N) for SENCO

SG2510	SG4100
--------	--------

DS530-D1 (10X0012N) for DeWalt

DW252	DW266
DW253	DW272
DW255	DW276
DW257	DCF624

DS530-M1 (10X0022N) for Makita

FS2200	XSF03*
FS2500	XSF04*
FS4200	XSF05*
FS6200	

*Canada - DFS452Z, DFS250Z, DFS251Z

INCLUDES

Auto-feed Attachment

Extension Pole

Adapter


Adjustable Handle

(3) Drive Bits

EA0314

EA0315

EA0316



3" AUTO-FEED SCREWDRIVER ATTACHMENT

The DS530 auto-feed screwdriver attachments are perfect for those looking to extend the reach of their existing power screwdrivers. The included extension pole turns your screwdriver into a stand-up tool, making it ideal for applications such as laying subfloor, underlayment, decking, cement board, and sheathing to steel. Capable of driving 1"-3" screws, the DS530 3" attachments are available in three models to quickly attach to select SENCO, DeWalt, and Makita screwdrivers.

TOOL OVERVIEW

- Feed On Return
- Patented Sliding Screw Guide
- Corner-Fit Feed System
- Quick Release Clamp
- Extension Pole
- Adjustable Depth-of-Drive with Depth Lock

APPLICATIONS

Sheathing, decking, underlayment, sub-flooring, steel decking, drywall, cement board, rigid foam insulation



5 YEAR
LIMITED
WARRANTY

3" AUTO-FEED SCREWDRIVER ATTACHMENT



-
- 1 FEED ON RETURN**
Screws are in place before you drive for faster and more consistent performance
 - 2 SLIDING SCREW GUIDE**
Prevents screw binding ensuring consistent feeds
 - 3 CORNER-FIT FEED SYSTEM**
For better line of sight, easier operation, and excellent corner access
 - 4 QUICK RELEASE CLAMP**
Easily change or replace bits
 - 5 EXTENSION POLE**
Provides extended reach for standing applications
 - 6 ADJUSTABLE DEPTH-OF-DRIVE WITH DEPTH LOCK**
For consistent flush or countersink drives
 - 7 STRIP FOLDBACK PROTECTION**
Prevents empty strip from jamming the tool
 - 8 TOOL-FREE ADJUSTABLE NOSEPIECE**
Single nosepiece for wood and drywall applications, with easy-to-read length markings
 - 9 ADJUSTABLE POWER GRIP HANDLE**
Durable and rotates 360°



F-LXP

#10Y0001N GRAINGER #793G48

SPECIFICATIONS

Trigger	Selectable
Technology	Fusion
Power Type	Cordless
Battery	18V Li-Ion
Charger	80% in 15 minutes, 100% in 45 minutes
Fasteners per Charge	650
Weight (with Battery)	6.8 lbs. (3.1 kg)
Height	12.5" (318 mm)
Length	10.4" (264mm)
Width	3.9" (99 mm)
Drive Cylinder	Aluminum

FASTENERS

Capacity	110
Range	$\frac{3}{8}$ " - $1\frac{1}{2}$ " (10mm - 38mm)
Gauge/ Crown	18 ga./ $\frac{1}{4}$ " (6mm)
Collation	Straight Glued Strip
Series	L

INCLUDES

VB0155 18V Li-Ion Battery
Charger
No-mar Pad
Storage Bag
2 Year Limited Warranty

SOLD SEPARATELY

Battery

VB0155	1.5Ah Replacement Battery
VB0190*	3.0Ah Battery

*The VB0189 charger is recommended for the VB0190 battery; using the VB0156 charger will result in longer charge times



1 1/2" 18 GA. 1/4" CROWN CORDLESS PNEUMATIC FINISH STAPLER

Experience the power and speed of traditional pneumatics with the portability and convenience of a cordless tool. This 18 gauge 1/4" crown finish stapler offers just that, featuring SENCO's patented Fusion Technology. The F-LXP delivers an immediate response to the trigger pull, driving up to 1 1/2" 18 gauge 1/4" crown finish staples with no ramp-up time in between shots.

TOOL OVERVIEW

- Fusion cordless air-power technology
- No hose, compressor or fuel cell
- Pneumatic-like response with no ramp-up time
- Jam reduction intelligence for fewer nail jams
- Selectable drive modes for bump fire or sequential firing
- Dry fire lockout
- Nose mounted LED light
- Tool-free depth-of-drive adjustment
- 18V Li-ion battery with LED charge indicator
- Adjustable belt hook with left or right side mount

APPLICATIONS

Cabinets, Soffits, Drawer Assembly

5 YEAR
LIMITED
WARRANTY

AVAILABLE THROUGH

GRAINGER
FOR THE ONES WHO GET IT DONE

FUSION
TECHNOLOGY

1½" 18 GA. ¼" CROWN CORDLESS PNEUMATIC FINISH STAPLER



#10Y0001N
F-LXP

- | | | |
|--|--|---|
| <p>1 FUSION CORDLESS AIR-POWER TECHNOLOGY
True pneumatic performance with no ramp-up time and the power to drive into the hardest substrates, including solid oak</p> | <p>5 NARROW NOSE DESIGN
Improves line of sight, includes no mar pad to protect woodwork</p> | <p>9 ALUMINUM DRIVE CYLINDER
Reduces weight and provides superior durability</p> |
| <p>2 SELECTABLE ACTUATION SWITCH
Easily and safely change from sequential to bump fire modes</p> | <p>6 LED LIGHT
Illuminates work surface</p> | <p>10 BATTERY STATUS LIGHTS
Quickly indicates battery power level</p> |
| <p>3 TOOL-FREE DEPTH-OF-DRIVE
Quickly adjust the depth for consistent flush or countersunk drives</p> | <p>7 18V LI-ION BATTERY
Fires up to 650 shots per full charge</p> | |
| <p>4 DRY FIRE LOCKOUT
Reduces tool wear and indicates the need to reload fasteners</p> | <p>8 REVERSIBLE & ADJUSTABLE BELT HOOK
Mounts on either side of tool</p> | |

Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on Senco fastening systems and how Senco will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: www.Senco.com.



DS225-18V

#10A0002N GRAINGER #820CA6



SPECIFICATIONS

RPM	0-5000
Torque	42 In-lbs
Voltage	18V
Weight w/ 3.0 Ah Battery	5.14 lbs
Height	9.59"
Length	13.66"
Width	3.36"
Drives Per Charge	2500
Warranty	5 Year Limited

FASTENERS

Screw Lengths	1" - 2"
Recommended Screw Diameters	#6 - #8
Drive Type	#2 Phillips, #2 Square, REX

*1/2" - 2" with nosepiece sold separately,
part #FC0822

INCLUDES

(2) Drive Bits
EA0297, EA0298



(2) 3.0 Ah Li-Ion
Extended Life Batteries

Charger

Storage Bag

2" 18V LI-ION 5000 RPM AUTO-FEED SCREWDRIVER

Powered by an efficient brushless motor, this high speed auto-feed screw gun includes two extended life 3.0 Ah batteries, a quick release feed system with our patented corner fit technology. The DS225-18V also features feed on return - the next screw is aligned with the bit for better line of sight and easier, more accurate screw placement.

TOOL OVERVIEW

- Patented corner-fit feed system
- Detachable feed system to expose bit for quick reversing
- 5000 RPM high torque brushless motor
- Precise depth of drive adjustment with depth lock
- Quick slide button bit change
- Two 3.0Ah Li-Ion extended life batteries included
- Quick charge battery charger
- Tool-free screw length adjustment
- Variable speed trigger with lock and reverse
- Adjustable belt hook

APPLICATIONS

For drywall (into wood or light gauge steel studs), subfloor, sheathing, cement board, and underlayment.



BRUSHLESS
MOTOR

5
YEAR
LIMITED
WARRANTY

DURASPIN™

2" 18V LI-ION 5000 RPM AUTO-FEED SCREWDRIVER



- | | | |
|--|--|--|
| 1 CORNER-FIT FEED SYSTEM
Improved line of sight and better corner access | 5 ADJUSTABLE DEPTH-OF-DRIVE WITH DEPTH LOCK
For consistent flush drive or countersink (knob is on the reverse side, not shown) | 9 QUICK TOGGLE REVERSE SWITCH
Easily switch between forward and reverse |
| 2 FEED ON RETURN
Screws are in place before you drive for faster and more consistent performance | 6 EXTENDED LIFE 3.0AH LI-ION BATTERY
Uses latest cell technology for increased power and capacity | 10 VARIABLE SPEED TRIGGER
Change RPMs for self-tapping screws into steel |
| 3 REMOVABLE FEED SYSTEM
Detachable feed system for easier reversing | 7 QUICK SLIDE BIT RELEASE
Easily insert or remove bits | 11 PATENTED SCREW GUIDE
Prevents screw binding for consistent feeding |
| 4 HIGH TORQUE BRUSHLESS MOTOR
Provides increased performance and battery life with reduced size | 8 1"-2" TOOL FREE ADJUSTABLE NOSE PIECE
Single nosepiece for wood and drywall applications with easy to read length markings | |

Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on Senco fastening systems and how Senco will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: www.Senco.com.



DS322-18V

#10C0002N GRAINGER #817G46



SPECIFICATIONS

RPM	0-1600, 0-2500
Torque	70 In-lbs
Voltage	18V
Weight w/ 3.0 Ah Battery	5.95 lbs
Height	9.59"
Length	14.52"
Width	3.36"
Drives Per Charge	2000
Warranty	5 Year Limited

FASTENERS

Screw Lengths	1" – 3"
Screw Diameters	#6 - #12
Drive Type	#2 Phillips, #2 Square, REX

*1/2" – 3" with nosepiece sold separately,
part #FC0887

INCLUDES

(2) Drive Bits
EA0400, EA0401



(2) 3.0 Ah Li-Ion
Extended Life Batteries

Charger

Storage Bag

3" 18V LI-ION 2500 RPM AUTO-FEED SCREWDRIVER

Powered by an efficient brushless motor, this high torque auto-feed screw gun includes two extended life 3.0 Ah batteries, a variable speed selector for heavy steel, a quick release feed system with our patented corner fit technology. The DS322-18V also features feed on return - the next screw is aligned with the bit for better line of sight and easier, more accurate screw placement.

TOOL OVERVIEW

- Patented corner-fit feed system
- Detachable feed system to expose bit for quick reversing
- Selectable 2500/1600 RPM high torque brushless motor
- Precise depth of drive adjustment with depth lock
- Quick slide button bit change
- Universal toe-nailing nosepiece
- Two 3.0Ah Li-Ion extended life batteries included
- Quick charge battery charger
- Tool-free screw length adjustment
- Variable speed trigger with lock and reverse
- Adjustable belt hook

APPLICATIONS

High torque applications including flooring, decking, docks, crating, gypsum/sheathing to steel, tile roofing.



BRUSHLESS
MOTOR

5
YEAR
LIMITED
WARRANTY

DURASPIN™

3" 18V LI-ION 2500 RPM AUTO-FEED SCREWDRIVER



#10C0002N

DS322-18V

- | | | |
|--|--|--|
| 1 CORNER-FIT FEED SYSTEM
Improved line of sight and better corner access | 5 SPEED SELECTION BUTTON (1600 RPM)
Quickly decrease the maximum speed for heavy steel applications | 9 1"-3" TOOL FREE ADJUSTABLE NOSE PIECE
Single nosepiece for wood and drywall applications with easy to read length markings |
| 2 FEED ON RETURN
Screws are in place before you drive for faster and more consistent performance | 6 ADJUSTABLE DEPTH-OF-DRIVE WITH DEPTH LOCK
For consistent flush drive or countersink (knob is on the reverse side, not shown) | 10 QUICK TOGGLE REVERSE SWITCH
Easily switch between forward and reverse |
| 3 REMOVABLE FEED SYSTEM
Detachable feed system for easier reversing | 7 EXTENDED LIFE 3.0AH LI-ION BATTERY
Uses latest cell technology for increased power and capacity | 11 VARIABLE SPEED TRIGGER
Change RPMs for self-tapping screws into steel |
| 4 HIGH TORQUE BRUSHLESS MOTOR
Provides increased performance and battery life with reduced size | 8 QUICK SLIDE BIT RELEASE
Easily insert or remove bits | 12 PATENTED SCREW GUIDE
Prevents screw binding for consistent feeding |

Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on Senco fastening systems and how Senco will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: www.Senco.com.



SPECIFICATIONS VB0212

Ampacity	2.0Ah / 37Wh
Voltage	18 vdc
Cell Type	18650
Height	2 ¼"
Length	5 ⅝"
Width	3 ½"
Weight	1.04 lbs

SPECIFICATIONS VB0210

Ampacity	4.0Ah / 72Wh
Voltage	18 vdc
Cell Type	21700
Height	2 ¼"
Length	5 ⅝"
Width	3 ½"
Weight	1.39 lbs

INCLUDES

Battery
Instruction Manual

SPECIFICATIONS VB0189

Output amperage	5A
Chemistry	Li-Ion
Height	5"
Length	8½"
Width	4"
Weight	1.8 lbs

INCLUDES

Charger
Instruction Manual

18V 2.0/4.0Ah LITHIUM-ION BATTERIES

VB0212, VB0210, VB0156 (GRAINGER #48J274)



2.0Ah/4.0Ah BATTERIES

SENCO batteries use highly efficient Li-ion cells and are compatible with all Senco DuraSpin and Fusion tools.

BATTERY OVERVIEW

- Ultra-bright LED's indicate state of charge, both on the tool or in the charger
- Rubberized overmold improves grip and withstands everyday jobsite abuse
- Cell design increases the performance of tools by lowering the internal resistance and keeps the battery outer profile small
- UL Certified



1 YEAR
LIMITED
WARRANTY

VB0189 BATTERY CHARGER



18V Li-ION CHARGER

Built with efficiency in mind, the Senco battery charger reaches 50% capacity in less than 20 minutes and 100% in less than 60 minutes. It stands upright on non-skid feet or can be mounted to the wall.

CHARGER OVERVIEW

- Built-in LED's indicate the state of charge, the condition of the attached battery and any temperature delay from elevated battery temperature
- Compatible with all Senco 18V Li-ion batteries
- UL listed in the US and Canada



1 YEAR
LIMITED
WARRANTY