



DS225-18V

#10A0001N



SPECIFICATIONS

RPM	0-5000
Torque	42 In-lbs
Voltage	18V
Weight w/ 3.0 Ah Battery	5.14 lbs
Height	9.59"
Length	13.66"
Width	3.36"
Drives Per Charge	2500
Warranty	5 Year Limited

FASTENERS

Screw Lengths	1" - 2"
Recommended Screw Diameters	#6 - #8
Drive Type	#2 Phillips, #2 Square, REX

*1/2" - 2" with nosepiece sold separately,
part #FC0822

INCLUDES

(2) Drive Bits
EA0297, EA0298



(2) 3.0 Ah Li-Ion
Extended Life Batteries

Charger

Storage Bag

2" 18V LI-ION 5000 RPM AUTO-FEED SCREWDRIVER

Powered by an efficient brushless motor, this high speed auto-feed screw gun includes two extended life 3.0 Ah batteries, a quick release feed system with our patented corner fit technology. The DS225-18V also features feed on return - the next screw is aligned with the bit for better line of sight and easier, more accurate screw placement.

TOOL OVERVIEW

- Patented corner-fit feed system
- Detachable feed system to expose bit for quick reversing
- 5000 RPM high torque brushless motor
- Precise depth of drive adjustment with depth lock
- Quick slide button bit change
- Two 3.0Ah Li-Ion extended life batteries included
- Quick charge battery charger
- Tool-free screw length adjustment
- Variable speed trigger with lock and reverse
- Adjustable belt hook

APPLICATIONS

For drywall (into wood or light gauge steel studs), subfloor, sheathing, cement board, and underlayment.



BRUSHLESS
MOTOR

5
YEAR
LIMITED
WARRANTY

DURASPIN™

2" 18V LI-ION 5000 RPM AUTO-FEED SCREWDRIVER



#10A0001N

DS225-18V

- | | | |
|--|--|--|
| <p>1 CORNER-FIT FEED SYSTEM
Improved line of sight and better corner access</p> | <p>5 ADJUSTABLE DEPTH-OF-DRIVE WITH DEPTH LOCK
For consistent flush drive or countersink (knob is on the reverse side, not shown)</p> | <p>9 QUICK TOGGLE REVERSE SWITCH
Easily switch between forward and reverse</p> |
| <p>2 FEED ON RETURN
Screws are in place before you drive for faster and more consistent performance</p> | <p>6 EXTENDED LIFE 3.0AH LI-ION BATTERY
Uses latest cell technology for increased power and capacity</p> | <p>10 VARIABLE SPEED TRIGGER
Change RPMs for self-tapping screws into steel</p> |
| <p>3 REMOVABLE FEED SYSTEM
Detachable feed system for easier reversing</p> | <p>7 QUICK SLIDE BIT RELEASE
Easily insert or remove bits</p> | <p>11 PATENTED SCREW GUIDE
Prevents screw binding for consistent feeding</p> |
| <p>4 HIGH TORQUE BRUSHLESS MOTOR
Provides increased performance and battery life with reduced size</p> | <p>8 1"-2" TOOL FREE ADJUSTABLE NOSE PIECE
Single nosepiece for wood and drywall applications with easy to read length markings</p> | |

Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on Senco fastening systems and how Senco will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: www.Senco.com.