



DS222-18V

#10B0002N GRAINGER #830H26



SPECIFICATIONS

RPM	0-1600, 0-2500
Torque	70 In-lbs
Voltage	18V
Weight w/ 4.0Ah Battery	5.65
Height	9.59"
Length	13.66"
Width	3.36"
Drives Per Charge	Up to 2500*
Warranty	5 Year Limited

*When driving #6 x 1 1/4" screws through drywall into wood

FASTENERS

Screw Lengths	1" - 2"***
Screw Diameters	#6 - #12
Drive Type	#2 Phillips, #2 Square, REX

***1/2" - 2" with nosepiece sold separately, part #FC0822

INCLUDES

(2) Drive Bits
EA0297, EA0298



4.0Ah Li-Ion
Extended Life Battery

Charger

Storage Bag

2" 18V LI-ION 2500 RPM AUTO-FEED SCREWDRIVER

Powered by an efficient brushless motor, this high torque auto-feed screw gun includes an extended life 4.0Ah battery and a variable speed selector for heavy steel, a quick release feed system with our patented corner fit technology. The DS222-18V also features feed on return - the next screw is aligned with the bit for better line of sight and easier, more accurate screw placement.

TOOL OVERVIEW

- Patented corner-fit feed system
- Detachable feed system to expose bit for quick reversing
- Selectable 2500/1600 RPM high torque brushless motor
- Precise depth of drive adjustment with depth lock
- Quick slide button bit change
- 4.0Ah Li-Ion extended life battery included
- Quick charge battery charger
- Tool-free screw length adjustment
- Variable speed trigger with lock and reverse
- Adjustable belt hook

APPLICATIONS

High torque applications including metal framing/decking, crating, and gypsum/sheathing to heavy steel.



2500
RPM/TPM

**BRUSHLESS
MOTOR**

5
YEAR
LIMITED
WARRANTY

DURASPIN™

2" 18V LI-ION 2500 RPM AUTO-FEED SCREWDRIVER



#10B0002N

DS222-18V

- | | | |
|--|--|--|
| 1 CORNER-FIT FEED SYSTEM
Improved line of sight and better corner access | 5 SPEED SELECTION BUTTON (1600 RPM)
Quickly decrease the maximum speed for heavy steel applications | 9 1'-2" TOOL FREE ADJUSTABLE NOSE PIECE
Single nosepiece for wood and drywall applications with easy to read length markings |
| 2 FEED ON RETURN
Screws are in place before you drive for faster and more consistent performance | 6 ADJUSTABLE DEPTH-OF-DRIVE WITH DEPTH LOCK
For consistent flush drive or countersink (knob is on the reverse side, not shown) | 10 QUICK TOGGLE REVERSE SWITCH
Easily switch between forward and reverse |
| 3 REMOVABLE FEED SYSTEM
Detachable feed system for easier reversing | 7 EXTENDED LIFE 4.0AH LI-ION BATTERY
Uses latest cell technology for increased power and capacity | 11 VARIABLE SPEED TRIGGER
Change RPMs for self-tapping screws into steel |
| 4 HIGH TORQUE BRUSHLESS MOTOR
Provides increased performance and battery life with reduced size | 8 QUICK SLIDE BIT RELEASE
Easily insert or remove bits | 12 PATENTED SCREW GUIDE
Prevents screw binding for consistent feeding |

Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on SENCO fastening systems and how SENCO will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: www.Senco.com.



DS230 SERIES

#9Z0011N | #9Z0012N | #9Z0021N
GRAINGER #60RJ87 | #60RJ88 | #60RJ89

SPECIFICATIONS

Weight	1.3 lbs
Height	5.53"
Length (vary by model)	10.34"-11"
Width	2.47"
Warranty	5 Year Limited

FASTENERS

Screw Lengths	1" – 2"
Screw Diameters	#6 - #12
Drive Type	#2 Phillips, #2 Square, REX

*1/2" – 2" with nosepiece sold separately,
part #FC0822

COMPATIBILITY

DS230-S1 (9Z0001N) for SENCO

SG2510	SG4100
--------	--------

DS230-M1 (9Z0021N) for Makita

FS2200	XSF03
FS2500	XSF04
FS4200	XSF05
FS6200	

DS230-D1 (9Z0011N) for DeWalt

DW252	DW266
DW253	DW272
DW255	DW276
DW257	

DS230-D2 (9Z0012N) for DeWalt

DCF620	DCF630
--------	--------

INCLUDES

(2) Drive Bits
EA0300, EA0301



Adaptor For DS230-D1*

* Not needed for other models



2" AUTO-FEED SCREWDRIVER ATTACHMENTS

Convert a standard screwdriver into an auto-feed screw system in seconds.

TOOL OVERVIEW

- Patented corner-fit feed system
- Feed on return functionality to improve speed and reliability of drives
- Universal nosepiece for drywall and wood applications
- Easily remove attachment to access bit
- Tool-free screw length adjustment
- Supports several screwdriver models
- Precise depth of drive adjustment with depth lock
- Light weight and compact

APPLICATIONS

Ideal for drywall (into wood or steel studs), metal framing, sheathing, cement board



Screwdriver
not included

5 YEAR
LIMITED
WARRANTY

2" AUTO-FEED ATTACHMENT



DS230 SERIES

- 1 CORNER-FIT FEED SYSTEM**
Improved line of sight and better corner access
- 2 FEED ON RETURN**
Screws are in place before you drive for faster and more consistent performance
- 3 REMOVABLE FEED SYSTEM**
Detachable feed system for easier reversing
- 4 1"-2" TOOL FREE ADJUSTABLE NOSE PIECE**
Single nosepiece for wood and drywall applications, with easy-to-read length markings
- 5 ADJUSTABLE DEPTH-OF-DRIVE WITH DEPTH LOCK**
For consistent flush drive or countersink (knob is on reverse side of attachment, not shown)
- 6 METAL FRAME**
For unmatched durability
- 7 SCREW GUIDE**
Prevents screw binding ensuring consistent feeding

Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on Senco fastening systems and how Senco will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: www.Senco.com.



DS530 SERIES

#10X0002N | #10X0012N | #10X0022N
GRAINGER | #793G46 | #793G47

SPECIFICATIONS

Weight	3.4 lbs. (1.5 kg)
Height	3.5" (89 mm)
Length	33" (838 mm)
Width	2.75" (70 mm)
Warranty	5 Year Limited

FASTENERS

Screw Lengths	1" - 3"
Screw Diameters	#6 - #12
Drive Type	#2 Phillips, #2 Square, REX

*½" - 1" with nosepiece sold separately,
part #FC0887

COMPATIBILITY

DS530-S1 (10X0002N) for SENCO

SG2510	SG4100
--------	--------

DS530-D1 (10X0012N) for DeWalt

DW252	DW266
DW253	DW272
DW255	DW276
DW257	DCF624

DS530-M1 (10X0022N) for Makita

FS2200	XSF03*
FS2500	XSF04*
FS4200	XSF05*
FS6200	

*Canada - DFS452Z, DFS250Z, DFS251Z

INCLUDES

Auto-feed Attachment

Extension Pole

Adapter

Adjustable Handle

(3) Drive Bits
EA0314
EA0315
EA0316



3" AUTO-FEED SCREWDRIVER ATTACHMENT

The DS530 auto-feed screwdriver attachments are perfect for those looking to extend the reach of their existing power screwdrivers. The included extension pole turns your screwdriver into a stand-up tool, making it ideal for applications such as laying subfloor, underlayment, decking, cement board, and sheathing to steel. Capable of driving 1"-3" screws, the DS530 3" attachments are available in three models to quickly attach to select SENCO, DeWalt, and Makita screwdrivers.

TOOL OVERVIEW

- Feed On Return
- Patented Sliding Screw Guide
- Corner-Fit Feed System
- Quick Release Clamp
- Extension Pole
- Adjustable Depth-of-Drive with Depth Lock

APPLICATIONS

Sheathing, decking, underlayment, sub-flooring, steel decking, drywall, cement board, rigid foam insulation



5 YEAR
LIMITED
WARRANTY

3" AUTO-FEED SCREWDRIVER ATTACHMENT



-
- 1 FEED ON RETURN**
Screws are in place before you drive for faster and more consistent performance
 - 2 SLIDING SCREW GUIDE**
Prevents screw binding ensuring consistent feeds
 - 3 CORNER-FIT FEED SYSTEM**
For better line of sight, easier operation, and excellent corner access
 - 4 QUICK RELEASE CLAMP**
Easily change or replace bits
 - 5 EXTENSION POLE**
Provides extended reach for standing applications
 - 6 ADJUSTABLE DEPTH-OF-DRIVE WITH DEPTH LOCK**
For consistent flush or countersink drives
 - 7 STRIP FOLDBACK PROTECTION**
Prevents empty strip from jamming the tool
 - 8 TOOL-FREE ADJUSTABLE NOSEPIECE**
Single nosepiece for wood and drywall applications, with easy-to-read length markings
 - 9 ADJUSTABLE POWER GRIP HANDLE**
Durable and rotates 360°



DS532-AC

#10X0003N GRAINGER #807HJ5

TOOL SPECIFICATIONS

RPM	0-2500
Amps	6.5
Cord Length	10 ft.
Clutch	Standard
Weight	7 lbs. (3.2 kg)
Height	7" (178 mm)
Length	40.5" (1029 mm)
Width	2.75" (70 mm)
Warranty	5 Year Limited

FASTENERS

Screw Lengths	1" - 3"**
Screw Diameters	#6 - #12
Drive Type	#2 Phillips, #2 Square, REX

*1/2" - 1" with nosepiece sold separately,
part #FC0887

INCLUDES

SG2510 High-Torque Screwdriver

DS530 3" Auto-Feed Attachment

Extension Pole

Adapter

Adjustable Handle

Storage Bag

(3) Drive Bits
EA0314
EA0315
EA0316



3" 2500 RPM SCREWDRIVER AND ATTACHMENT KIT

The extremely versatile DS532-AC 3-in-1 screwdriver kit provides configurations for a variety of applications. The high-torque, adjustable motor of the included SG2510 screwdriver is capable of speeds up to 2500 rpm, making it an ideal choice for driving 1"-3" screws into dense materials such as wood and composite decking, cement board, and sheathing to steel. The kit comes complete with SG2510 screwdriver, DS530 auto-feed attachment, extension pole, 3 bits and storage bag.

TOOL OVERVIEW

- 3-in-1 Tool Kit
- Feed On Return
- Patented Sliding Screw Guide
- Corner-Fit Feed System
- High-torque 0-2500 RPM motor
- Quick Release Clamp

APPLICATIONS

For wood and composite decking, cement board, sub-flooring and underlayment, sheathing to steel, steel decking, drywall to wood or steel



5 YEAR
LIMITED
WARRANTY

DURASPIN™

3" 2500 RPM SCREWDRIVER AND ATTACHMENT KIT



-
- | | |
|--|--|
| 1 FEED ON RETURN
Screws are in place before you drive for faster and more consistent performance | 6 EXTENSION POLE
Provides extended reach for standing applications |
| 2 SLIDING SCREW GUIDE
Prevents screw binding ensuring consistent feeds | 7 ADJUSTABLE DEPTH-OF-DRIVE WITH DEPTH LOCK
For consistent flush or countersink drives |
| 3 CORNER-FIT FEED SYSTEM
For better line of sight, easier operation, and excellent corner access | 8 STRIP FOLDBACK PROTECTION
Prevents empty strip from jamming the tool |
| 4 HIGH-TORQUE 0-2500 RPM MOTOR
Easily powers through the densest materials | 9 TOOL-FREE ADJUSTABLE NOSEPIECE
Single nosepiece for wood and drywall applications, with easy-to-read length markings |
| 5 QUICK RELEASE CLAMP
Easily change or replace bits | 10 ADJUSTABLE POWER GRIP HANDLE
Durable and rotates 360° |
-

CONFIGURATIONS

3 tools in 1:



Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on SENCO fastening systems and how SENCO will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: www.Senco.com.



DS225-18V

#10A0002N GRAINGER #820CA6



SPECIFICATIONS

RPM	0-5000
Torque	42 In-lbs
Voltage	18V
Weight w/ 3.0 Ah Battery	5.14 lbs
Height	9.59"
Length	13.66"
Width	3.36"
Drives Per Charge	2500
Warranty	5 Year Limited

FASTENERS

Screw Lengths	1" - 2"
Recommended Screw Diameters	#6 - #8
Drive Type	#2 Phillips, #2 Square, REX

*1/2" - 2" with nosepiece sold separately,
part #FC0822

INCLUDES

(2) Drive Bits
EA0297, EA0298



(2) 3.0 Ah Li-Ion
Extended Life Batteries

Charger

Storage Bag

2" 18V LI-ION 5000 RPM AUTO-FEED SCREWDRIVER

Powered by an efficient brushless motor, this high speed auto-feed screw gun includes two extended life 3.0 Ah batteries, a quick release feed system with our patented corner fit technology. The DS225-18V also features feed on return - the next screw is aligned with the bit for better line of sight and easier, more accurate screw placement.

TOOL OVERVIEW

- Patented corner-fit feed system
- Detachable feed system to expose bit for quick reversing
- 5000 RPM high torque brushless motor
- Precise depth of drive adjustment with depth lock
- Quick slide button bit change
- Two 3.0Ah Li-Ion extended life batteries included
- Quick charge battery charger
- Tool-free screw length adjustment
- Variable speed trigger with lock and reverse
- Adjustable belt hook

APPLICATIONS

For drywall (into wood or light gauge steel studs), subfloor, sheathing, cement board, and underlayment.



BRUSHLESS
MOTOR

5
YEAR
LIMITED
WARRANTY

DURASPIN™

2" 18V LI-ION 5000 RPM AUTO-FEED SCREWDRIVER



#10A0001N

DS225-18V

- | | | |
|--|--|--|
| 1 CORNER-FIT FEED SYSTEM
Improved line of sight and better corner access | 5 ADJUSTABLE DEPTH-OF-DRIVE WITH DEPTH LOCK
For consistent flush drive or countersink (knob is on the reverse side, not shown) | 9 QUICK TOGGLE REVERSE SWITCH
Easily switch between forward and reverse |
| 2 FEED ON RETURN
Screws are in place before you drive for faster and more consistent performance | 6 EXTENDED LIFE 3.0AH LI-ION BATTERY
Uses latest cell technology for increased power and capacity | 10 VARIABLE SPEED TRIGGER
Change RPMs for self-tapping screws into steel |
| 3 REMOVABLE FEED SYSTEM
Detachable feed system for easier reversing | 7 QUICK SLIDE BIT RELEASE
Easily insert or remove bits | 11 PATENTED SCREW GUIDE
Prevents screw binding for consistent feeding |
| 4 HIGH TORQUE BRUSHLESS MOTOR
Provides increased performance and battery life with reduced size | 8 1"-2" TOOL FREE ADJUSTABLE NOSE PIECE
Single nosepiece for wood and drywall applications with easy to read length markings | |

Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on Senco fastening systems and how Senco will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: www.Senco.com.



DS322-18V

#10C0001N GRAINGER #817G30



SPECIFICATIONS

RPM	0-1600, 0-2500
Torque	70 In-lbs
Voltage	18V
Weight w/ 3.0 Ah Battery	5.95 lbs
Height	9.59"
Length	14.52"
Width	3.36"
Drives Per Charge	2000
Warranty	5 Year Limited

FASTENERS

Screw Lengths	1" – 3"
Screw Diameters	#6 - #12
Drive Type	#2 Phillips, #2 Square, REX

*1/2" – 3" with nosepiece sold separately,
part #FC0887

INCLUDES

(2) Drive Bits
EA0400, EA0401



(2) 3.0 Ah Li-Ion
Extended Life Batteries

Charger

Storage Bag

3" 18V LI-ION 2500 RPM AUTO-FEED SCREWDRIVER

Powered by an efficient brushless motor, this high torque auto-feed screw gun includes two extended life 3.0 Ah batteries, a variable speed selector for heavy steel, a quick release feed system with our patented corner fit technology. The DS322-18V also features feed on return - the next screw is aligned with the bit for better line of sight and easier, more accurate screw placement.

TOOL OVERVIEW

- Patented corner-fit feed system
- Detachable feed system to expose bit for quick reversing
- Selectable 2500/1600 RPM high torque brushless motor
- Precise depth of drive adjustment with depth lock
- Quick slide button bit change
- Universal toe-nailing nosepiece
- Two 3.0Ah Li-Ion extended life batteries included
- Quick charge battery charger
- Tool-free screw length adjustment
- Variable speed trigger with lock and reverse
- Adjustable belt hook

APPLICATIONS

High torque applications including flooring, decking, docks, crating, gypsum/sheathing to steel, tile roofing.



BRUSHLESS
MOTOR

5
YEAR
LIMITED
WARRANTY

DURASPIN™

3" 18V LI-ION 2500 RPM AUTO-FEED SCREWDRIVER



#10C0001N

DS322-18V

- | | | |
|--|--|--|
| 1 CORNER-FIT FEED SYSTEM
Improved line of sight and better corner access | 5 SPEED SELECTION BUTTON (1600 RPM)
Quickly decrease the maximum speed for heavy steel applications | 9 1"-3" TOOL FREE ADJUSTABLE NOSE PIECE
Single nosepiece for wood and drywall applications with easy to read length markings |
| 2 FEED ON RETURN
Screws are in place before you drive for faster and more consistent performance | 6 ADJUSTABLE DEPTH-OF-DRIVE WITH DEPTH LOCK
For consistent flush drive or countersink (knob is on the reverse side, not shown) | 10 QUICK TOGGLE REVERSE SWITCH
Easily switch between forward and reverse |
| 3 REMOVABLE FEED SYSTEM
Detachable feed system for easier reversing | 7 EXTENDED LIFE 3.0AH LI-ION BATTERY
Uses latest cell technology for increased power and capacity | 11 VARIABLE SPEED TRIGGER
Change RPMs for self-tapping screws into steel |
| 4 HIGH TORQUE BRUSHLESS MOTOR
Provides increased performance and battery life with reduced size | 8 QUICK SLIDE BIT RELEASE
Easily insert or remove bits | 12 PATENTED SCREW GUIDE
Prevents screw binding for consistent feeding |

Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on Senco fastening systems and how Senco will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: www.Senco.com.