



SFT10XP





GRAINGER #48LR37


TOOL SPECIFICATIONS


Trigger	Sequential, Auto
Op. Pressure	60-95 psi (4.1 - 6.5 bar)
Air Consumption (60 CPM)	.77 scfm
Air Inlet	1/4" NPT
Weight	2.1 lbs (.955 kg)
Height	6.57" (167 mm)
Length	8.58" (218 mm)
Width	1.65" (42 mm)
Main Body Material	Aluminum


FASTENER SPECIFICATIONS

Capacity	92-110
Collation	Straight glued strip

A		D	
	Series A-wire 22 ga.		D-wire 22 ga.
Length 1/4" - 1/2"		5/8"	
Crown 3/16"		3/16"	

B	
	Series B-wire 22 ga.
Length 1/4" - 1/2"	
Crown 1/2"	

C	
	Series C-wire 22 ga.
Length 1/4" - 5/8"	
Crown 3/8"	

E	
	Series E-wire 20 ga.
Length 3/8" - 5/8"	
Crown 3/16"	




ITEM # SFT10XP-A/D (3/16" Crown, 22 Ga.): 6S0001N
SFT10XP-A/D AUTO (3/16" Crown, 22 Ga.): 6S0101N
SFT10XP-B (1/2" Crown, 22 Ga.): 6S0011N
SFT10XP-C (3/8" Crown, 22 Ga.): 6S0021N
SFT10XP-C AUTO (3/8" Crown, 22 Ga.): 6S0121N
SFT10XP-E (3/16" Crown, 20 Ga.): 6S0031N
SFT10XP-F (1/2" Crown, 20 Ga.): 6S0041N
SFT10XP-G (3/8" Crown, 20 Ga.): 6S0051N

Compact and durable, the SFT10XP delivers best-in-class performance for a variety of fine wire stapling applications. Models drive staples ranging in length from 5/32" to 5/8". With a robust all-metal motor construction and ergonomic design, this tool works all day, every day and won't snag or scuff fabric.

APPLICATIONS

- Upholstery, felt, casebacks, screening and shoes

G	
	Series G-wire 2) ga.
Length 1/4" - 5/8"	
Crown 3/8"	

FEATURES AND BENEFITS

- Heavy-duty steel cap
- Short trigger stroke
- Rear exhaust keeps oil off fabric
- Automatic models have adjustable speed triggers

INCLUDES

- 5 year limited warranty



SFT10XP

20-22 Ga.Fine Wire Upholstery Stapler



SOLD SEPARATELY

PARTS KIT

YK0802	Piston stop kit
YK0803	Firing System Kit
YK0804	Firing System Kit (AUTO)

Choose the right actuation mode

Sequential Actuation (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tool to ensure proper use and safety precautions. For additional information on SENCO fastening systems and how SENCO will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at:



FinishPro® 25XP

GRAINGER #21U136

18_{GA}

TOOL SPECIFICATIONS

Trigger	Sequential
Op. Pressure	70-120 psi (4.8 - 8.3 bar)
Air Consumption (60 CPM)	1.92 scfm
Air Inlet	¼" NPT
Weight	2.7 lbs (1.2 kg)
Height	9.9" (251 mm)
Length	9.8" (249 mm)
Width	2.2" (56 mm)
Main body material	Aluminum

FASTENER SPECIFICATIONS

AX, AY Series	5/8" - 2 1/8"
Capacity	110
Range	5/8" - 2 1/8" (16mm - 54mm)
Shank/Gauge	.0468"/18 ga.
Collation	Straight glued strip
Series	AX, AY

INCLUDES

- 5 year limited warranty
- Case, no-mar pad

SOLD SEPARATELY

PARTS KIT

YK0281	Firing system kit
YK0282	Piston stop kit



2 1/8" Brad Nailer

ITEM #760102N

The durable, powerful tool that redefined the 18 ga. brad nailer category. Metal construction with a never-lube design makes it tough and easy to operate. Also ultra-versatile drive both slight and medium headed 18ga. brads from 5/8" to 2 1/8" into the hardest woods.

APPLICATIONS

- Finish & Woodworking, Cabinets, Paneling, Casing

FEATURES AND BENEFITS

- NeverLube® design - no lubrication required
- Drives slight and medium head 18 gauge brads
- Powerful - ensures complete drives into hard substrates
- Tool-free depth-of-drive adjustment
- Include: overmold comfort grip, overmold trigger, adjustable exhaust, and belt hook



FinishPro® 25XP

2 1/8" Brad Nailer

ITEM #760102N



Adjustable Exhaust
no tools required.

Aluminum Mainbody
lightweight and maneuverable
at only 2.7 lbs.

Tool-Free Adjustable
Depth-of-Drive
drives nails to a consistent and
controllable depth.

Last Brad Lock Out
lengthens the life of the tool.

No-Mar Pad & Square Nose Safety
protects work surface and the square nose
safety design keeps the tool from slipping
out of position.

Overmold Grip
for comfortable all-day operation.

NeverLube® Design
requires no tool oil.

Overmold Trigger
reduces fatigue.

Reversible Belt Hook
mounts to left or right side of tool.

Construction Ruler
for quick measurements.



Choose the right actuation mode

Sequential Actuation (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tool to ensure proper use and safety precautions. For additional information on SENCO fastening systems and how SENCO will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: senco.com



FinishPro® 42XP

GRAINGER #21U129

15_{GA}

TOOL SPECIFICATIONS

Trigger	Sequential
Op. Pressure	70-120 psi (4.8 - 8.3 bar)
Air Consumption (60 CPM)	3.87 scfm
Air Inlet	¼" NPT
Weight	4.7 lbs (2.1 kg)
Height	11.25" (286 mm)
Length	13" (330 mm)
Width	3.5" (89 mm)
Main body material	Magnesium

FASTENER SPECIFICATIONS

DA Series	1¼" - 2½"
-----------	-----------

Capacity	104
Range	1¼" - 2½" (32mm - 65mm)
Shank/Gauge	.072/15 ga.
Collation	30°-34° angled taped strip
Series	DA

INCLUDES

- 5 year limited warranty
- Case, no-mar pad, belt hook and contact trigger kit

SOLD SEPARATELY

PARTS KIT

YK0362	Repair kit
--------	------------



2½" 34° Angled Finish Nailer

ITEM #4G0001N

The marquee tool for professional finish carpenters! The FinishPro®42XP features a lightweight magnesium mainbody, a Never-Lube® design, and a rugged internal engine design for comfortable, consistent, long-lasting operation. Drives 1¼" to 2½" nails into the hardest woods.

APPLICATIONS

- Finish and trim

FEATURES AND BENEFITS

- Never-Lube® design - no oil required
- EZ-Clear™ latch virtually eliminates downtime caused by fastener jams
- Metal cylinder for increased durability
- Tool-free depth-of-drive adjustment

AVAILABLE THROUGH

GRAINGER®
FOR THE ONES WHO GET IT DONE

FinishPro[®] 42XP

2½" 34° Angled Finish Nailer

ITEM #4G0001N



360° Rotatable Exhaust
no tools required, quiet design.

Over-Molded Rubber Grip
for comfortable all-day operation.

Magnesium Mainbody
provides a durable and ultra light
tool for comfortable extended use.

Never-Lube[®] Design
eliminates oil carryover
onto the work surface.

Metal Cylinder
for increased durability.

Tool-free Depth-of-Drive
perfectly countersink fastener

EZ-Clear[™] Latch
virtually eliminates downtime
caused by fastener jams.

Belt Hook
lets the tool go where you go

No-mar Pad
protects work surface.



Choose the right actuation mode

Sequential Actuation (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tool to ensure proper use and safety precautions. For additional information on SENCO fastening systems and how SENCO will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: senco.com



BN31M1P
BRAD NAILER
GRAINGER #48LR72



SPECIFICATIONS

Trigger	Selectable
Op. Pressure	70-120 psi (4.8 - 8.3 bar)
Air Consumption (60 CPM)	2.4 scfm
Air Inlet	¼" NPT
Weight	3.0 lbs (1.4 kg)
Height	9.75" (248 mm)
Length	10.5" (267 mm)
Width	2.5" (65 mm)
Main Body Material	Aluminum

FASTENERS

Series	AX
Capacity	110
Range	⅝"-2⅛" (16mm - 55mm)
Shank/ Gauge	.047" (1.19mm)/ 18 ga
Collation	Straight glued strip

INCLUDES

Carrying Case
¼" Fitting

SOLD SEPARATELY

Parts Kit
YK0908 Repair Kit

2⅛" BRAD NAILER

The durable and lightweight BN31M1P is equipped with a number of quality-of-life features that make it ideal for all-day use. The tool comes outfitted with a dry fire lockout, which reduces wear on the tool and indicates when to reload. Additionally, SENCO's oil-less design saves the user the hassle of oiling the tool prior to use, saving you time and money. Capable of driving 18-gauge brad nails from ⅝" to 2⅛" in length, this nailer is ideal for finish and trim applications where you want the power to drive through dense materials without splitting the work surface.

TOOL OVERVIEW

- Oil-less design eliminates the need for routine lubrication
- Dry fire lockout reduces tool wear and indicates when to reload
- Selectable trigger to switch between contact or sequential firing modes
- Quick clear latch to easily clear jams or misfeeds
- Tool-free depth adjustment for consistent flush or countersunk drives

APPLICATIONS

Finish and trim, woodworking, paneling, casing, molding, chair rail, decorative trim.

2 1/8" BRAD NAILER



BN31M1P

BRAD NAILER

- | | | |
|---|---|---|
| 1 OIL-LESS DESIGN
Routine lubrication is not required. Saving you time with daily maintenance | 5 TOOL-FREE DEPTH ADJUSTMENT
For consistent flush or countersunk drives | 9 NO-MAR PAD
Protects the worksurface from being scratched or damaged. Extra no-mar pad included. |
| 2 DRY FIRE LOCKOUT
Reduces tool wear and indicates the need to reload fasteners | 6 360° ADJUSTABLE EXHAUST
Directs air away from the operator and worksurface | 10 RELOAD INDICATOR
Allows the user to quickly identify when it's time to reload (not visible, on reverse side of tool) |
| 3 SELECTABLE TRIGGER
Makes it easy to switch between contact or sequential firing modes | 7 ROTATABLE BELT HOOK
Provides quick right/left hand access when needed | 11 SWIVEL PLUG
For added maneuverability |
| 4 QUICK CLEAR LATCH
Remove jams or misfeeds without the use of a tool | 8 ERGONOMIC OVERMOLDED GRIP
Reduces fatigue and increases control of the tool | 12 ALUMINUM MAINBODY
Durable and lightweight |

Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on Senco fastening systems and how Senco will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: www.Senco.com.




SC2

GRAINGER #48LR01

TOOL SPECIFICATIONS

Trigger	Sequential
Op. Pressure	80-110 psi (5.5 - 7.5 bar)
Air Consumption (60 CPM)	3.7 scfm
Air Inlet	3/8" NPT
Weight	6.9 lbs (3.1 kg)
Height	9.44" (240 mm)
Length	12.5" (318 mm)
Width	2" (50.8 mm)
Main body material	Aluminum

FASTENER SPECIFICATIONS



Capacity	80
Range	1/4" - 1/2" (7mm - 13mm)
Crown	1"
Collation	Straight glued strip
Series	X

INCLUDES

- 5 year limited warranty

SOLD SEPARATELY

PARTS KIT

YK0371	Repair kit
--------	------------



Sencor® Corrugated Fastener

ITEM #470001N

The powerful corrugated fastener for hard and dense materials. The versatile SC2 clamps material together and drives three sizes of fasteners for stronger joints. Plus, it eliminates gluing, milling, doweling, screwing and clamping. Takes 1" crown, 1/4" to 1/2" fasteners.

APPLICATIONS

- Joint fastening in wood, crate, pallet, truss & box assembly



FEATURES AND BENEFITS

- Powerful for hard and dense material.
- Eliminate gluing, milling, doweling, screwing and clamping
- Added Strength for larger butt joints.
- Eliminate milling, doweling, clamping, screwing and other time-consuming, cost adding operations
- Sencor® corrugated fasteners provide twice the joint strength of ordinary fasteners

AVAILABLE THROUGH
GRAINGER
FOR THE ONES WHO GET IT DONE



SHF200
GRAINGER #48LR45

16
GA

TOOL SPECIFICATIONS

Trigger	Sequential actuation
Op. Pressure	90-110 psi (6.2 - 7.6 bar)
Air Consumption (60 CPM)	2.52 scfm
Air Inlet	1/4" NPT
Weight	10.1 lbs (4.58 kg)
Height	21.5" (546 mm)
Length	17.8" (452 mm)
Width	3.1" (78 mm)
Main Body Material	Aluminum

FASTENER SPECIFICATIONS

RW Series	1 1/2" - 2"
Capacity	107
Range	1 1/2" - 2" (38mm - 50mm)
Shank	.072
Collation	16 ga. straight glued strip
Series	RW

INCLUDES

- 5 year limited warranty
- Case, mallet, oil, wrenches and 1/4" air fitting



2" Hardwood Flooring Nailer

ITEM# 8D0001N

The SHF200 is a professional-grade pneumatic hardwood flooring cleat nailer. It provides consistent driving power for flush, professional-quality installation. It uses 1 1/2" - 2" L-shaped cleats that hold the wood securely yet allow for seasonal expansion and contraction. The long ergonomically designed handle helps minimize user fatigue.

APPLICATIONS

- Installation of 1/2" and 3/4" thick hardwood and hardwood laminate flooring.

FEATURES AND BENEFITS

- Easy on the arm, it's pneumatic action requires a single strike to drive fastener
- Innovative non-marring base that adjust between 1/2" and 3/4" flooring without the use of tools
- Lightweight and well-balanced, yet 5% more powerful than competitive flooring nailers
- Safety trigger prevents accidental ejection of fasteners
- Extra-long ergonomic handle reduces the amount the operator has to bend over

AVAILABLE THROUGH
GRAINGER
FOR THE ONES WHO GET IT DONE

SHF200

2" Hardwood Flooring Nailer

ITEM# 8D0001N



Pneumatic Driving Action
Consistently drives fastener for easier installation.

Angled Air Fitting
hose does not interfere with magazine or operator.

Hardened Driver Blade
for longer life.

Rear Load Magazine
drives 0.063" L-type cleats in 1-1/2", 1-3/4" and 2" lengths.

Tool-Free Base Adjustment
unique base design allows user to rotate base to desired thickness without additional tools.

Ergonomic Design
longer handle helps minimize user fatigue.

Balance for Stability
tool sits upright for smoother floor installation.

Mallet Actuated
mallet actuated firing simultaneously sets floor boards (tongue and groove) and drives cleat into material groove.

Aluminum Housing
robust housing design.

Includes Non Marring Mallet.



Choose the right actuation mode

Sequential Actuation (also known as restrictive trigger or trigger fire) operates in the following a sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tool to ensure proper use and safety precautions. For additional information on Senco fastening systems and how Senco will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: senco.com



TN11G1
PIN NAILER
GRAINGER #792UV9

SPECIFICATIONS

Trigger	Sequential Dual Trigger
Op. Pressure	70-100 psi (4.8 - 6.9 bar)
Air Consumption (60 CPM)	1.1 scfm
Air Inlet	1/4" NPT
Weight	2.41 lbs (1.09 kg)
Height	7.8" (198 mm)
Length	8.57" (218 mm)
Width	2.6" (66 mm)
Main Body Material	Aluminum

FASTENERS

CZ Series	1/2"-1 3/8"
Capacity	100
Range	1/2"-1 3/8" (12.7mm - 35.5mm)
Shank/ Gauge	.0267/23 ga.
Collation	Straight glued strip
Series	A1, CZ

INCLUDES

Case
Swivel Air Plug
Wrench



1 3/8" 23 GAUGE PINNER

Featuring SENCO's Neverlube® oil-free design, the tool never needs to be lubricated, eliminating stains to the work surface. SENCO's 1-3/8" 23-gauge pin nailer allows you to fasten intricate millwork, casing, and other pieces of trim without splitting or requiring any touch up work. This 23-gauge headless pinner drives 1/2" to 1-3/8" pins into dense hardwoods commonly used in various moldings.

TOOL OVERVIEW

- Neverlube® oil-free design
- Magazine automatically adjusts for fastener length
- Ergonomic angled "pistol-grip" handle
- Ultra-narrow nosepiece
- Reversible belt hook
- Last nail lockout

APPLICATIONS

Fine wood working, molding and decorative trim.



NEVERLUBE®
OIL FREE TOOL



1 3/8" 23 GAUGE PINNER



TN11G1
PIN NAILER

- | | | |
|--|---|---|
| 1 NEVERLUBE® OIL-FREE DESIGN
Maintenance-free operation, eliminating the risk of oil spillover onto the work surface | 4 ULTRA-NARROW NOSEPIECE
Easy access to tight corners and other hard to reach areas | 7 REAR EXHAUST WITH EMBEDDED MUFFLER
Includes 1/4" swivel air plug |
| 2 MAGAZINE ADJUSTS TO FASTENERS
Automatically conforms to fit different pin lengths | 5 REVERSIBLE BELT HOOK
Mounts to either side of the tool for right or left handed use | 8 LOW LOAD INDICATOR
Shows when it's time to reload (on reverse side of tool) |
| 3 ERGONOMIC ANGLED "PISTOL-GRIP" HANDLE
Improves control of the tool for comfortable all-day operation | 6 LAST NAIL LOCKOUT
Prevents dry-firing | 9 DUAL TRIGGER
Added safety precaution to prevent accidental fires |

Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on SENCO fastening systems and how SENCO will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: www.Senco.com.



TN21L1
PIN NAILER
GRAINGER #792UW0

SPECIFICATIONS

Trigger	Sequential Dual Trigger
Op. Pressure	70-110 psi (4.8 - 7.6 bar)
Air Consumption (60 CPM)	1.1 scfm
Air Inlet	1/4" NPT
Weight	3.16 lbs (1.43 kg)
Height	9.2" (233 mm)
Length	8.76" (222 mm)
Width	2.6" (66 mm)
Main Body Material	Aluminum

FASTENERS

ZX Series	5/8"-2"
Capacity	200
Range	5/8"-2" (15mm - 50mm)
Shank/ Gauge	.0294/21 ga.
Collation	Straight glued strip
Series	ZX

INCLUDES

Case
Swivel Air Plug
Wrench



2" 21 GAUGE PINNER

Featuring SENCO's Neverlube® oil-free design, the tool never needs to be lubricated, eliminating stains to the work surface. SENCO's 2" 21-gauge pinner is capable of shooting 5/8" to 2" slight head pins. The 21-gauge offers more holding power than a 23-gauge tool and leaves a smaller hole than an 18-gauge brad nailer, creating the perfect middle ground between the two.

TOOL OVERVIEW

- Neverlube® oil-free design
- Magazine automatically adjusts for fastener length
- Ergonomic angled "pistol-grip" handle
- Ultra-narrow nosepiece
- Reversible belt hook
- Last nail lockout

APPLICATIONS

Fine wood working, molding and decorative trim.



NEVERLUBE®
OIL FREE TOOL



2" 21 GAUGE PINNER



TN21L1
PIN NAILER

- | | | |
|--|---|---|
| 1 NEVERLUBE® OIL-FREE DESIGN
Maintenance-free operation, eliminating the risk of oil spillover onto the work surface | 4 ULTRA-NARROW NOSEPIECE
Easy access to tight corners and other hard to reach areas | 7 REAR EXHAUST WITH EMBEDDED MUFFLER
Includes 1/4" swivel air plug |
| 2 MAGAZINE ADJUSTS TO FASTENERS
Automatically conforms to fit different pin lengths | 5 REVERSIBLE BELT HOOK
Mounts to either side of the tool for right or left handed use | 8 LOW LOAD INDICATOR
Shows when it's time to reload (on reverse side of tool) |
| 3 ERGONOMIC ANGLED "PISTOL-GRIP" HANDLE
Improves control of the tool for comfortable all-day operation | 6 LAST NAIL LOCKOUT
Prevents dry-firing | 9 DUAL TRIGGER
Added safety to prevent accidental fires |

Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on Senco fastening systems and how Senco will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: www.Senco.com.



F-LXP

#10Y0001N GRAINGER #793G48

SPECIFICATIONS

Trigger	Selectable
Technology	Fusion
Power Type	Cordless
Battery	18V Li-Ion
Charger	80% in 15 minutes, 100% in 45 minutes
Fasteners per Charge	650
Weight (with Battery)	6.8 lbs. (3.1 kg)
Height	12.5" (318 mm)
Length	10.4" (264mm)
Width	3.9" (99 mm)
Drive Cylinder	Aluminum

FASTENERS

Capacity	110
Range	$\frac{3}{8}$ " - $\frac{1}{2}$ " (10mm - 38mm)
Gauge/ Crown	18 ga./ $\frac{1}{4}$ " (6mm)
Collation	Straight Glued Strip
Series	L

INCLUDES

VB0155 18V Li-Ion Battery
Charger
No-mar Pad
Storage Bag
2 Year Limited Warranty

SOLD SEPARATELY

Battery	
VB0155	1.5Ah Replacement Battery
VB0190*	3.0Ah Battery

*The VB0189 charger is recommended for the VB0190 battery; using the VB0156 charger will result in longer charge times



1½" 18 GA. ¼" CROWN CORDLESS PNEUMATIC FINISH STAPLER

Experience the power and speed of traditional pneumatics with the portability and convenience of a cordless tool. This 18 gauge ¼" crown finish stapler offers just that, featuring SENCO's patented Fusion Technology. The F-LXP delivers an immediate response to the trigger pull, driving up to 1½" 18 gauge ¼" crown finish staples with no ramp-up time in between shots.

TOOL OVERVIEW

- Fusion cordless air-power technology
- No hose, compressor or fuel cell
- Pneumatic-like response with no ramp-up time
- Jam reduction intelligence for fewer nail jams
- Selectable drive modes for bump fire or sequential firing
- Dry fire lockout
- Nose mounted LED light
- Tool-free depth-of-drive adjustment
- 18V Li-ion battery with LED charge indicator
- Adjustable belt hook with left or right side mount

APPLICATIONS

Cabinets, Soffits, Drawer Assembly

5 YEAR
LIMITED
WARRANTY

AVAILABLE THROUGH
GRAINGER
FOR THE ONES WHO GET IT DONE

FUSION
TECHNOLOGY

1½" 18 GA. ¼" CROWN CORDLESS PNEUMATIC FINISH STAPLER



#10Y0001N
F-LXP

- | | | |
|--|--|---|
| <p>1 FUSION CORDLESS AIR-POWER TECHNOLOGY
True pneumatic performance with no ramp-up time and the power to drive into the hardest substrates, including solid oak</p> | <p>5 NARROW NOSE DESIGN
Improves line of sight, includes no mar pad to protect woodwork</p> | <p>9 ALUMINUM DRIVE CYLINDER
Reduces weight and provides superior durability</p> |
| <p>2 SELECTABLE ACTUATION SWITCH
Easily and safely change from sequential to bump fire modes</p> | <p>6 LED LIGHT
Illuminates work surface</p> | <p>10 BATTERY STATUS LIGHTS
Quickly indicates battery power level</p> |
| <p>3 TOOL-FREE DEPTH-OF-DRIVE
Quickly adjust the depth for consistent flush or countersunk drives</p> | <p>7 18V LI-ION BATTERY
Fires up to 650 shots per full charge</p> | |
| <p>4 DRY FIRE LOCKOUT
Reduces tool wear and indicates the need to reload fasteners</p> | <p>8 REVERSIBLE & ADJUSTABLE BELT HOOK
Mounts on either side of tool</p> | |

Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on Senco fastening systems and how Senco will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: www.Senco.com.



LS61H1P **FINISH STAPLER**



SPECIFICATIONS

Trigger	Selectable
Op. Pressure	70-120 psi (4.8 - 8.3 bar)
Air Consumption (60 CPM)	2.4 scfm
Air Inlet	¼" NPT
Weight	3.1 lbs (1.4 kg)
Height	9.5" (241 mm)
Length	10.25" (260 mm)
Width	2.5" (65 mm)
Main Body Material	Aluminum

FASTENERS

Series	L
Capacity	110
Range	⅜" - 1½" (10mm - 38mm)
Gauge	18
Crown	¼" (6mm)
Collation	Straight glued strip

INCLUDES

Carrying Case
¼" Fitting

SOLD SEPARATELY

Parts Kit
YK0908 Repair Kit

¼" CROWN, 1½" FINISH STAPLER

The LS61H1P is an 18-gauge finish stapler that drives ¼" crown staples from ⅜" to 1½" in length. Convenience features like SENCO's oil-less design eliminates the need for routine lubrication. This stapler is ideal for woodworking, cabinetry, and both internal and external trim applications.

TOOL OVERVIEW

- Oil-less design eliminates the need for routine lubrication
- Selectable trigger to switch between contact or sequential firing modes
- Tool-free depth adjustment for consistent flush or countersunk drives
- 360° adjustable exhaust directs air away from the operator or worksurface
- Rotatable belt hook for quick right/left hand access

APPLICATIONS

Woodworking, cabinets, soffits, drawer assembly.



1/4" CROWN, 1 1/2" FINISH STAPLER



LS61H1P
FINISH STAPLER

- | | | |
|---|--|--|
| 1 OIL-LESS DESIGN
Routine lubrication is not required. Saving you time with daily maintenance | 5 ROTATABLE BELT HOOK
Provides quick right/left hand access when needed | 9 SWIVEL PLUG
For added maneuverability |
| 2 SELECTABLE TRIGGER
Makes it easy to switch between contact or sequential firing modes | 6 ERGONOMIC OVERMOLDED GRIP
Reduces fatigue and increases control of the tool | 10 ALUMINUM MAINBODY
Durable and lightweight |
| 3 TOOL-FREE DEPTH ADJUSTMENT
For consistent flush or countersunk drives | 7 NO-MAR PAD
Protects the worksurface from being scratched or damaged. Extra no-mar pad included. | |
| 4 360° ADJUSTABLE EXHAUST
Directs air away from the operator and worksurface | 8 RELOAD INDICATOR
Allows the user to quickly identify when it's time to reload (not visible, on reverse side of tool) | |

Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on Senco fastening systems and how Senco will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: www.Senco.com.