



FinishPro®18BMg

18 GA

TOOL SPECIFICATIONS

Trigger	Selectable
Op. Pressure	70-120 psi (4.8 - 8.3 bar)
Air Consumption (60 CPM)	1.6 scfm
Air Inlet	¼" NPT
Weight	2.8 lbs (1.26 kg)
Height	9.8" (248 mm)
Length	10" (255 mm)
Width	2.5" (63.5 mm)
Main body material	Magnesium

FASTENER SPECIFICATIONS



Capacity	100
Range	5/8" - 2 1/8" (16mm - 50mm)
Shank/Gauge	.0468"/18 ga.
Collation	Straight glued strip
Series	AX

INCLUDES

- 5 year limited warranty
- Case, swivel air plug and wrench

SOLD SEPARATELY

PARTS KIT

YK0868	Repair kit
--------	------------



2 1/8" Magnesium Brad Nailer
ITEM #9B0001N

The FinishPro®18BMg drives 2 1/8" 18 gauge brad nails. It is extremely lightweight with a magnesium body, virtually maintenance free with oil free operation, and is equipped with a nose-mounted LED light to help illuminate dark work spaces. A feature-rich tool designed and built for the professional.

APPLICATIONS

- Chair rails, baseboards, case backs, cabinetry, furniture repair, small trim and craft assembly

FEATURES AND BENEFITS

- Magnesium mainbody provides a durable and ultra light
- Oil-free motor eliminates oil carryover onto the work surface
- Nose mounted LED light illuminates dark work spaces
- Selectable trigger lets you control the fastening method
- 360° adjustable rear exhaust and belt hook
- Over-molded rubber grip, swivel plug and reload indicator

FinishPro[®]18BMg

2 1/8" Magnesium Brad Nailer

ITEM# 9B0001N



Oil-less Design

eliminates oil carryover onto the work surface

Magnesium Mainbody
durable and ultra-light

Selectable Trigger

select between contact or sequential triggers with a flip of a switch

Nose mounter LED light
illuminates work surface

EZ-Clear[™] Latch
clears jams fast

No-mar pad
protects work surface

Rubber Comfort Grip
reduces vibration and fatigue, increases productivity

Rear Exhaust
360° rotation

Belt hook Rotates 360°
lets the tool go where you go

Tool-free Adjustable Depth-of-Drive
achieve the right depth of countersink

Composite Magazine
durable and light

Low load Indicator
easy to see when it's time to reload

Choose the right actuation mode

Sequential Actuation (also known as restrictive trigger or trigger fire) operates in the following a sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tool to ensure proper use and safety precautions. For additional information on SENCO fastening systems and how SENCO will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: senco.com