



FN81T1 **FRAMING NAILER**

SPECIFICATIONS


Trigger	Sequential
Op. Pressure	70-120 psi (4.8 - 8.3 bar)
Air Consumption (60 CPM)	6.7 scfm
Air Inlet	3/8" NPT
Weight	8.75 lbs (3.9 kgs)
Height	14.13" (358 mm)
Length	20.75" (527 mm)
Width	4.88" (123 mm)
Main Body Material	Aluminum
Warranty	5 Years

FASTENERS

Capacity	63
Length	2" or 3 1/2"
Shank	.113" - .148"
Collation	20° Angled Tape Strip
Series	GD, HD, KD, MD, GL, HL

INCLUDES

No-Mar Pad
Air Plug
Belt Hook



3 1/2" FULL ROUND HEAD FRAMING NAILER

The FN81T1 delivers the power and durability demanded by professional contractors for all-day performance on the toughest jobsites. It drives a wide range of plastic collated nails from .113" to .148" in diameter, and 2"-3 1/2" in length. Upgraded features include, an ergonomic design, an in-line magazine for clear line of sight and a tool-free depth of drive for quick adjustments.

TOOL OVERVIEW

- Best in class tool power & durability
- Well-balanced ergonomic design
- In-line magazine for optimal line of sight
- Aggressive toenail safety
- Tool-free depth of drive
- Engineered and Assembled in Cincinnati, Ohio

APPLICATIONS

Framing, truss building, sub flooring, sheathing, decking, siding, fencing, pallets and crate assembly



PNEUMATIC FRAMER VIDEO
Tool in use



PNEUMATIC FRAMER VIDEO
Product overview

20°


21°

22°



5 YEAR
LIMITED
WARRANTY

3 1/2" FULL ROUND HEAD FRAMING NAILER



FN81T1
FRAMING NAILER

- | | | |
|---|---|---|
| 1 ERGONOMIC DESIGN
Superb balance for all-day use | 4 AGGRESSIVE TOENAIL SAFETY
Provides extra grip for toenail applications, no-mar tip included | 7 RUGGED RAFTER HOOK
Rotatable, aluminum design keeps the tool secure when not in use |
| 2 POWERFUL
Consistently drives a full range of nails | 5 TOOL-FREE DEPTH OF DRIVE
Quickly and easily set the drive depth | 8 DRY FIRE LOCKOUT
Reduces tool wear and indicates the need to reload fasteners |
| 3 IN-LINE MAGAZINE
Provides clear line of sight for right and left handed operators, improves balance and reduces fatigue | 6 OVERMOLD GRIP
Increases control of the tool, accelerating productivity | 9 REAR TWO-STEP LOADING
Allows for rapid reloads for both right and left handed operators |

Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on SENCO fastening systems and how SENCO will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: www.Senco.com.