



FinishPro® 25XP

18_{GA}

TOOL SPECIFICATIONS

Trigger	Sequential
Op. Pressure	70-120 psi (4.8 - 8.3 bar)
Air Consumption (60 CPM)	1.92 scfm
Air Inlet	¼" NPT
Weight	2.7 lbs (1.2 kg)
Height	9.9" (251 mm)
Length	9.8" (249 mm)
Width	2.2" (56 mm)
Main body material	Aluminum

FASTENER SPECIFICATIONS

AX, AY Series	5/8" - 2 1/8"
Capacity	110
Range	5/8" - 2 1/8" (16mm - 54mm)
Shank/Gauge	.0468"/18 ga.
Collation	Straight glued strip
Series	AX, AY

INCLUDES

- 5 year limited warranty
- Case, no-mar pad

SOLD SEPARATELY

PARTS KIT

YK0281	Firing system kit
YK0282	Piston stop kit



2 1/8" Brad Nailer

ITEM #760102N

The durable, powerful tool that redefined the 18 ga. brad nailer category. Metal construction with a never-lube design makes it tough and easy to operate. Also ultra-versatile drive both slight and medium headed 18ga. brads from 5/8" to 2 1/8" into the hardest woods.

APPLICATIONS

- Finish & Woodworking, Cabinets, Paneling, Casing

FEATURES AND BENEFITS

- NeverLube® design - no lubrication required
- Drives slight and medium head 18 gauge brads
- Powerful - ensures complete drives into hard substrates
- Tool-free depth-of-drive adjustment
- Include: overmold comfort grip, overmold trigger, adjustable exhaust, and belt hook

FinishPro® 25XP

2 1/8" Brad Nailer

ITEM #760102N



Adjustable Exhaust
no tools required.

Aluminum Mainbody
lightweight and maneuverable
at only 2.7 lbs.

Tool-Free Adjustable
Depth-of-Drive
drives nails to a consistent and
controllable depth.

Last Brad Lock Out
lengthens the life of the tool.

No-Mar Pad & Square Nose Safety
protects work surface and the square nose
safety design keeps the tool from slipping
out of position.

Overmold Grip
for comfortable all-day operation.

NeverLube® Design
requires no tool oil.

Overmold Trigger
reduces fatigue.

Reversible Belt Hook
mounts to left or right side of tool.

Construction Ruler
for quick measurements.



Choose the right actuation mode

Sequential Actuation (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tool to ensure proper use and safety precautions. For additional information on SENCO fastening systems and how SENCO will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: senco.com