



FinishPro® 42XP

15 GA

TOOL SPECIFICATIONS

Trigger	Sequential
Op. Pressure	70-120 psi (4.8 - 8.3 bar)
Air Consumption (60 CPM)	3.87 scfm
Air Inlet	¼" NPT
Weight	4.7 lbs (2.1 kg)
Height	11.25" (286 mm)
Length	13" (330 mm)
Width	3.5" (89 mm)
Main body material	Magnesium

FASTENER SPECIFICATIONS



Capacity	104
Range	1¼" - 2½" (32mm - 65mm)
Shank/Gauge	.072/15 ga.
Collation	30°-34° angled taped strip
Series	DA

INCLUDES

- 5 year limited warranty
- Case, no-mar pad, belt hook and contact trigger kit

SOLD SEPARATELY

PARTS KIT

YK0362	Repair kit
--------	------------



2½" 34° Angled Finish Nailer

ITEM #4G0001N

The marquee tool for professional finish carpenters! The FinishPro®42XP features a lightweight magnesium mainbody, a Never-Lube® design, and a rugged internal engine design for comfortable, consistent, long-lasting operation. Drives 1¼" to 2½" nails into the hardest woods.

APPLICATIONS

- Finish and trim

FEATURES AND BENEFITS

- Never-Lube® design – no oil required
- EZ-Clear™ latch virtually eliminates downtime caused by fastener jams
- Metal cylinder for increased durability
- Tool-free depth-of-drive adjustment

FinishPro[®] 42XP

2½" 34° Angled Finish Nailer

ITEM #4G0001N



360° Rotatable Exhaust
no tools required, quiet design.

Over-Molded Rubber Grip
for comfortable all-day operation.

Magnesium Mainbody
provides a durable and ultra light
tool for comfortable extended use.

Never-Lube[®] Design
eliminates oil carryover
onto the work surface.

Metal Cylinder
for increased durability.

Tool-free Depth-of-Drive
perfectly countersink fastener

EZ-Clear[™] Latch
virtually eliminates downtime
caused by fastener jams.

No-mar Pad
protects work surface.

Belt Hook
lets the tool go where you go

Choose the right actuation mode

Sequential Actuation (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tool to ensure proper use and safety precautions. For additional information on SENCO fastening systems and how SENCO will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: senco.com