

Features:

- Heavy Duty OSHA spaced guards, corrosion resistant polyester coating
- Aluminum props matched to motor for optimum efficiencies
- Motor Type: TEAO, IP55 rated, thermally protected, ball bearings
- Fans oscillate approx. 90 degrees
- Heavy gauge, adjustable height pedestals: safety yellow
- Pre-wired with 10ft cord, 115v plug end



Model:
24R6Y370-OSC



Model:
36PY2-OSC

Pedestal: Yellow

Specifications

Model #	Prop Dia.	Prop Type	HP	Ph	Volts	Hz	High Amps	High CFM	Spd	High RPM	Guard Type	Guard Color	Mount Type	Sones @ 5 Ft
24R6Y370-OSC	24"	3 Wing	1/2	1	115	60	5.9	6450	2	1075	OSHA	Yellow	Fan Only	7.1
30R6Y370-OSC	30"	3 Wing	1/2	1	115	60	5.9	8710	2	1075	OSHA	Yellow	Fan Only	7.01
36R6Y370-OSC	36"	3 Wing	1/2	1	115	60	5.9	11250	2	1075	OSHA	Yellow	Fan Only	8.79
24PY2-OSC	24"	3 Wing	1/2	1	115	60	5.9	6450	2	1075	OSHA	Yellow	Pedestal	7.1
30PY2-OSC	30"	3 Wing	1/2	1	115	60	5.9	8710	2	1075	OSHA	Yellow	Pedestal	7.01
36PY2-OSC	36"	3 Wing	1/2	1	115	60	5.9	11250	2	1075	OSHA	Yellow	Pedestal	8.79

Performance

