



NS20XP


17_{GA}**16**_{GA}

TOOL SPECIFICATIONS

Trigger	Contact
Op. Pressure	70-120 psi (4.8 - 8.3 bar)
Air Consumption (60 CPM)	3.5 scfm
Air Inlet	3/8" NPT
Weight	5.1 lbs. (2.3 kg)
Height	11" (279 mm)
Length	15" (381 mm)
Width	3.5" (89 mm)
Main Body Material	Aluminum

FASTENER SPECIFICATIONS

Capacity	160
Collation	Straight glued and taped strip



Series	O-wire 17 ga.
Length	1" - 2"
Crown	7/16"



Series	N-wire 16 ga.
Length	1" - 2"
Crown	7/16"

INCLUDES

- 5 year limited warranty

SOLD SEPARATELY

PARTS KIT

YK0840	Firing system kit
YK0841	Piston stop kit
HC0788	Siding safety kit



16-17 Ga. Heavy Wire Staplers

ITEM #9X0001N

Setting the new standard for class leading power and tool durability, the NS20XP is the industry benchmark for construction staplers.

The new drive track design allows for superior control of the fastener, providing unrivaled drivability. The NS20XP drives both 16 and 17 gauge, 7/16" crown staples (1" to 2" in length).

APPLICATIONS

- Sheathing, furniture framing, roof decking, subflooring, crate and box assembly, pallets, cedar shingles, furring, fascia and soffits and ridge beam assembly

FEATURES AND BENEFITS

- 15% more powerful than all other construction staplers in its class
- Enhanced EZ-Clear™ latch allows for quick access to clear fasteners and a NEW aggressive locking feature provides superior holding power for complete control of the fastener, offering pinpoint accuracy and unrivaled driveability.
- New drive track design eliminates movement of the staple, enhancing overall drive performance and virtually eliminating fastener jams, skipping and misfires.
- Rotatable belt hook
- Convert your NS20XP into a vinyl siding stapler

NS20XP

16-17 Gauge Heavy Wire Staplers

ITEM #9X0001N



15% More Powerful
than all other construction
staplers in its class.

Aluminum Mainbody
weighs just 5.1 lbs. for ease
of use and maneuverability.

Soft Over-molded Palm Grip
reduces fatigue, increases productivity.

Rotatable Belt Hook

Well Balanced
ergonomic design for all-day use.

Formed steel latch
ensures accurate, jam-free
staple drives into all substrates.

Multi-Directional Stitching
up to 14 staples per second.

Steel Staple Door
provides enhanced durability and
improved drive.



Vinyl Siding Attachment (Sold Separately)

Convert NS20XP into vinyl siding stapler.
Order Item #HC0788

Choose the right actuation mode

Sequential Actuation (also known as restrictive trigger or trigger fire) operates in the following a sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tool to ensure proper use and safety precautions. For additional information on Senco fastening systems and how Senco will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: senco.com