




FinishPro®18 SPECIFICATIONS

Item #	1U0001N
Trigger	Contact
Op. Pressure	70-95 psi (4.8 - 6.6 bar)
Air Inlet	1/4" NPT
Weight	3.1 lbs (1.6 kg)
Height	9.3" (238 mm)
Length	9.75" (248 mm)
Main body material	Aluminum

PC1010 COMPRESSOR SPECIFICATIONS

Power source: Electric	
Moter:	Induction
Max. amp:	4 amps @115V
Horsepower:	1/2 hp.(running)
Pump:	Oil-less
SCFM @ 90 psi:	0.7
Pump-up time:	125 seconds
Recovery time:	30 seconds
Max pressure:	135 psi
Tank storage:	1 gallon
Weight:	20 lbs. (9.07 kg)
Dimensions:	length 14", height 13", width 10"

FASTENER SPECIFICATIONS



Capacity	110
Range	5/8" - 2" (16mm - 50mm)
Shank/Gauge	.0468"/18 ga.
Collation	Straight glued strip
Series	AY

INCLUDES

- 1 year limited warranty
- Hose, tool oil, air fittings, safety glasses, wrenches, variety pack of 18 ga. nails

PC0947 COMBO KIT

18_{GA}

18 Ga. Brad Nailer Combo Kit

ITEM #PC0947

Everything to get you started on your finish project. 1-gallon PC1010 compressor, a 2" FinishPro 18 ga. brad nailer, coil hose, air fittings, safety glasses and fasteners in one kit.

APPLICATIONS

- Interior trim, cabinets, chair rail, crown molding, baseboards, book shelves and exterior trim

FEATURES AND BENEFITS

FinishPro18

- 2", 18 ga. brand nailer
- With adjustable depth-of-drive control, adjustable exhaust, belt hook, soft grip and no-mar pad - for your convenience

PC1010 Compressor

- 1/2 hp.(running), 1 gal. oil-less motor compressor
- 4 amps @ 115V, 120 PSI Max Output
- 1/4" quick disconnect coupler and regulator
- Individual gauges for tank and regulated output pressure
- Lightweight - 20 lbs. (9.09 kg)

SOLD SEPARATELY

PARTS KIT

YK0393

Repair kit

PC0947 COMBO KIT

18 Ga. Brad Nailer Combo Kit

ITEM #PC0947



Choose the right actuation mode

Sequential Actuation (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tool to ensure proper use and safety precautions. For additional information on SENCO fastening systems and how SENCO will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: senco.com