



# PS15XP


16 GA

## TOOL SPECIFICATIONS

|                          |                            |
|--------------------------|----------------------------|
| Trigger                  | Contact                    |
| Op. Pressure             | 70-120 psi (4.8 - 8.3 bar) |
| Air Consumption (60 CPM) | 3.18 scfm                  |
| Air Inlet                | 3/8" NPT                   |
| Weight                   | 5.5 lbs (2.5 kg)           |
| Height                   | 9" (229 mm)                |
| Length                   | 15.25" (387 mm)            |
| Width                    | 4" (105 mm)                |
| Main Body Material       | Aluminum                   |



## FASTENER SPECIFICATIONS



|           |                       |
|-----------|-----------------------|
| Capacity  | 160                   |
| Length    | 5/8" - 1 1/2"         |
| Gauge     | 16                    |
| Crown     | 1"                    |
| Collation | Taped and taped glued |
| Series    | P-wire                |

## INCLUDES

- 5 year limited warranty

## SOLD SEPARATELY

### PARTS KITS

|                |                           |
|----------------|---------------------------|
| YK0784, YK0818 | Repair kits               |
| YK0883         | Block out kit             |
| YJ0044         | Retrofit kit-solid safety |

## 1" Wide Crown, 1 1/2" Heavy Wire Stapler

ITEM #9T0001N

Constructed of durable, high strength components, the PS15XP has been developed for extreme performance and longevity. The NEW drive track design allows for superior control of the fastener and unrivaled driveability. Drives 1" crown 16 ga. staples from 5/8" to 1 1/2".

## APPLICATIONS

- Wire lathing, foam insulation board, furniture, cabinet frames, butt-joints and corrugated carton to skid

## FEATURES AND BENEFITS

- Enhanced EZ-Clear™ latch allows for quick access to clear fasteners and a NEW aggressive locking feature provides superior holding power for complete control of the fastener, offering pinpoint accuracy and unrivaled driveability
- NEW Drive track design eliminates movement of the staple, enhancing overall drive performance and virtually eliminating fastener jams, skipping and misfires
- Robust firing valve design makes the tool fast, powerful, efficient, and easy to maintain
- Positive-locking adjustable depth-of-drive ensures consistently flush drives and helps prevent overdrives

# PS15XP

## 1" Wide Crown 1½" Heavy Wire Stapler

ITEM #9T0001N



### Choose the right actuation mode

**Sequential Actuation** (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

**Contact Actuation** (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tool to ensure proper use and safety precautions. For additional information on SENCO fastening systems and how SENCO will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: [senco.com](http://senco.com)