



PalletPro™57FXP 15°

TOOL SPECIFICATIONS

Trigger	Contact
Op. Pressure	70-120 psi (4.9 - 8.4 bar)
Air Consumption (60 CPM)	3.07 scfm
Air Inlet	3/8" NPT
Weight	5.9 lbs (2.67 kg)
Height	11.25" (286 mm)
Length	11.88" (302 mm)
Width	5.25" (123 mm)
Main body material	Aluminum

FASTENER SPECIFICATIONS



Capacity	300-350
Range	1" - 2 1/4" (25mm - 57mm)
Shank/Gauge	.082"-.092"
Collation	15° flat wire wound coil
Series	BK, ED, EJ, EL, SE

INCLUDES

- 5 year limited warranty
- Wrenches, tool oil

SOLD SEPARATELY

PARTS KIT

YK0446	Repair kit
--------	------------



2 1/4" Heavy-Duty Coil Nailer

ITEM #4L0001N

Has the ability to drive up to 2 1/4" nails into hardwood reliably and consistently. The PalletPro57FXP coil nailer is built for high speed, high volume operations with a fastener capacity of 300 to 350. Features include a high durability driver and piston bumper and body protection.

APPLICATIONS

- Boxes, carton-to-skid, crates and pallets

FEATURES AND BENEFITS

- High capacity composite magazine - fast and easy loading
- Ultra-durability driver and piston bumper designed for long life
- Adjustable nail canister accommodates wide range of nails
- Reversed safety element for improved line of sight
- Body protection - side steel wearplates reduce abrasion of tool

PalletPro™ 57FXP

2¼" Heavy-Duty Coil Nailer

ITEM #4L0001N



360° Adjustable Exhaust
no tool required.

Body Protection
side steel wearplates reduce abrasion of tool

Aluminum Mainbody
weighs 5.9 lbs.

Rugged Driver & Piston Bumper
for improved performance and durability.

Tool-Free Depth-of-Drive
adjustment delivers perfectly
countersunk fasteners into a variety of
materials.

Comfort Grip
for comfortable all-day operation.

High Capacity
Composite Magazine
fast and easy loading

NOTE:
Only accepts flat wire wound nails

Debris Shield
protects user and work surface.



Choose the right actuation mode

Sequential Actuation (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tool to ensure proper use and safety precautions. For additional information on SENCO fastening systems and how SENCO will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: senco.com