



QUICK CHANGE HAMMERS & TIPS




Quick
Change
Hammer
w/4 tips



Quick
Change
Dead Blow
Hammer



Quick
Change
Hammer



Replaceable
interchangeable
tips – soft to
extra hard

QUICK CHANGE HAMMER WITH 4 TIPS

Soft face 1 lb. **Quick Change** hammer with four tips is engineered to perform better than rubber or plastic face hammers. Nupla's patented Smart Hammer® technology features a non-ferrous slug-loaded composite cavity within the head which is fully encased in a tough polymer outer jacket. The hammer handle is solid Nuplaglas® made through a pultrusion process that uses a unique resin and thousands of strands of fiberglass - becoming resistant to weather and chemicals. The hammer/holder with tips is surface-protective and completely non-marring. It has an ergonomic soft vinyl cushion grip. Safe to use all year round, this hammer/holder offers a superior level of ergonomic efficiency. Set includes four 1.5" interchangeable, replaceable color-coded tips: soft medium hard, hard and extra hard.

QUICK CHANGE DEAD BLOW HAMMER/HOLDERS

Power Drive Dead blow hammer/holders are engineered to perform better than rubber or plastic face hammers. Nupla's patented Smart Hammer® technology features a shot-loaded composite cavity within the head which is fully encased in a tough polymer outer jacket. When the hammer is struck, the free flowing inner shot concentrates striking power and increases driving force creating a dead blow effect. No rebound upon impact transfers full energy of the blow to the object being struck. Hammers are surface protective, abrasion- and impact-resistant. Hammer handles are solid Nuplaglas® with ergonomic non-slip grips. They deliver more power, less rebound and vibration shock reducing the risk of musculoskeletal disorders. Safe to use all year round, the hammer/holders offer a superior level of ergonomic efficiency. Use the holders with interchangeable, replaceable tips from super soft to extra hard.

QUICK CHANGE HAMMER/HOLDERS

Soft face hammer/holders are engineered to perform better than rubber or plastic face hammers. Nupla's patented Smart Hammer® technology features a slug-loaded composite cavity within the head which is fully encased in a tough polymer outer jacket. Hammers are surface protective, abrasion- and impact-resistant. Hammer handles are solid Nuplaglas® with non-slip grips. They deliver more power, less rebound and vibration shock reducing the risk of musculoskeletal disorders. Safe to use all year round, the hammer/holders offer a superior level of ergonomic efficiency. Use the holders with interchangeable, replaceable tips from super soft to extra hard.

AVAILABLE THROUGH

GRAINGER
FOR THE ONES WHO GET IT DONE

QUICK CHANGE HAMMERS

COMP. NUPLA	PART PART	GRAINGER PART	PART DESCRIPTION	Tip Dia.	Tip Type	Tip Material	Head Weight		Head Length	Overall Length
				(in.)			(oz.)	(lbs.)	(in.)	(in.)
			QUICK CHANGE HAMMERS							
02549	6894100		Quick-Change Clamshell Pack - 1 lb hammer, four 1.5 dia. QC tips (soft, medium, hard, extra-hard)	1 1/2	Extra-Hard/Hard/Medium/Soft	Nonmarring Plastic	16	1	4	12 1/2
03356	6894196		1.5" dia., 1lb Quick-Change Impax Dead Blow Hammer , C grip, no tips	1 1/2	-	-	17	1 1/16	4 1/8	12 5/8
03360	6894202	5LV12	2" dia., 2 lb Quick-Change Impax Dead Blow Hammer , C grip, no tips	2	-	-	22	1.35	4 1/2	13 1/2
03365	6894203		2.5" dia., 4lb. Quick-Change Impax Dead Blow Hammer , C grip, no tips	2 1/2	-	-	36	2.25	5	14 1/2
07607	6894186		3" dia., 6lb Quick-Change Impax Dead Blow Hammer , SG grip, no tips	3	-	-	96	6	5 5/8	15 1/2
09400	6894191		4lb Quick-Change Hammer, 3" dia, C grip, no tips	3	-	-	64	2 1/4	3 3/4	15
09405	6894192	5LV16	6lb Quick-Change Hammer, 3" dia, C grip, no tips	3	-	-	96	4 1/4	3 3/4	15
09500	6894197	2LMX8	1.5 lb Quick-Change Hammer, 2" dia, C grip, no tips	2	-	-	17	1 1/16	2 5/8	13 1/2
09505	6894173	3MD70	2.25lb Quick-Change Hammer, 2" dia, C grip, no tips	2	-	-	36	1 1/4	2 3/4	14
09510	6894171		2.5lb Quick-Change Hammer, 2.5" dia, C grip, no tips	2 1/2	-	-	36	1 1/4	3 1/4	15
09550	6894172		1lb Quick-Change Hammer, 1.5" dia, C grip, no tips	1 1/2	-	-	7	7/16	2 3/8	12 1/2
09555	6894198		1.25lb Quick-Change Hammer, 1.5" dia, C grip, no tips	1 1/2	-	-	16	1	2 1/8	12 1/2
09600	6894199		6oz Quick-Change Hammer, 1" dia, C grip, no tips	1	-	-	6	3/8	2	11 7/8
09605	6894128	6D050	9oz Quick-Change Hammer, 1" dia, C grip, no tips	1	-	-	4	1/4	2	11

QUICK CHANGE TIPS

Tips are available in hardness from super soft to extra hard and brass and cover a multitude of applications. Interchangeable, replaceable, used with Nupla Dead Blow Quick Change and Quick Change hammer/holders.

Tip applications and features:

Super Soft (grey): Used for interior vehicle use (door panels) and assembly applications of soft composites, plastics, and soft alloy metals to eliminate surface scratching, denting, or fracturing. **Replaces rubber and vinyl tips.**

Soft (brown): Used for interior vehicle use (door panels) and assembly applications of soft composites, plastics, and soft alloy metals to eliminate surface scratching, denting, or fracturing. **Replaces rubber, wood, soft lead, and brass tips.**

Medium (red): Used for exterior vehicle use (trim) and assembly applications of soft composites, plastics, and soft alloy metals to eliminate surface scratching, denting, or fracturing. **Replaces rawhide, wood, lead, and plastic tips.**

Tough (green): Used for exterior vehicle use (trim) and assembly applications of soft composites, plastics, and soft alloy metals to eliminate surface scratching, or fracturing. **Replaces hard wood, brass, lead, rawhide and plastic tips.**

Medium Hard (cream): Used for brake service (rotors/drums), aluminum engine and body components to eliminate potential surface damage. Also for assembly applications of hard alloy metals or composites and tempered steels to eliminate surface scratching, denting, or fracturing. **Replaces hard wood, rawhide and soft metal tips.**

Hard (black): Used for brake service (rotors/drums), aluminum engine and body components to eliminate potential surface damage. Also for assembly applications of hard alloy metals or composites and tempered steels to eliminate surface scratching, denting, or fracturing. **Replaces rawhide, plastic, micarta and fiber tips.**

Extra Hard (yellow): Used for brake service (rotors/drums), aluminum engine and body components to eliminate potential surface damage. Also for assembly applications of hard alloy metals or composites and tempered steels to eliminate surface scratching, denting, or fracturing. **Replaces rawhide, micarta, fiber, and copper tips.**

Brass: The 1.5" tip is made of injection molded vinyl with brass face. It is used for axle and suspension service (steel, engine and body components) and light steel face or brass hammer applications. Also used for assembly applications of hard surface composites and other hard materials or alloys. Caution: these are not surface protective striking tips.

AVAILABLE THROUGH

GRAINGER
FOR THE ONES WHO GET IT DONE

QUICK CHANGE TIPS

PART NUMBER	GRAINGER PART	TIPS FOR QUICK CHANGE HAMMERS	Tip Dia.	Hardness	Material	Color	Thread size	Fits Hammers
			(in.)				(in.)	(in.)
		Tips						
6894131		1" dia. Quick-Change Tip, red, medium	1	Medium	Vinyl	Red	1/4-20	6D050
6894132		1" dia. Quick-Change Tip, green, tough	1	Tough	Vinyl	Green	1/4-20	6D050
6894134		1" dia. Quick-Change Tip cream, medium-hard	1	Medium-Hard	Nylon	Cream	1/4-20	6D050
6894133		1" dia. Quick-Change Tip, black, hard	1	Hard	Nylon	Black	1/4-20	6D050
6894194		1" dia. Quick-Change Tip, yellow, extra-hard	1	Extra-Hard	Nylon	Yellow	1/4-20	2LMY1
6894130		1.5" dia. Quick-Change Tip, brown, soft	1 1/2	Soft	Vinyl	Brown	5/16-18	3MD69
6894129		1.5" dia. Quick-Change Tip, red, medium	1 1/2	Medium	Vinyl	Red	5/16-18	3MD69
6894113		1.5" dia. Quick-Change Tip, green, tough	1 1/2	Tough	Vinyl	Green	5/16-18	3MD69
6894114	4A114	1.5" dia. Quick-Change Tip, cream, medium hard	1 1/2	Medium-Hard	Nylon	Cream	5/16-18	3MD69
6894115		1.5" dia. Quick-Change Tip, black, hard	1 1/2	Hard	Nylon	Black	5/16-18	3MD69
6894195	2LMX6	1.5" dia. Quick-Change Tip, yellow, extra hard	1 1/2	Extra-Hard	Nylon	Yellow	5/16-18	2LMX7, 2LMX8
6894164		1.5" dia. Quick-Change Tip, hardened steel face	1 1/2	Extra-Hard	Hardened Steel	Steel	5/16-18	3MD69
6894116		2" dia. Quick-Change Tip, green, tough	2	Tough	Vinyl	Green	3/8-16	3MD70, 5LV12
6894117		2" dia. Quick-Change Tip, cream, medium-hard	2	Medium-Hard	Nylon	Cream	3/8-16	3MD70, 5LV12
6894118		2" dia. Quick-Change Tip, black, hard	2	Hard	Nylon	Black	3/8-16	3MD70, 5LV12
6894165		2" dia. Quick-Change Tip, hardened steel face	2	Extra-Hard	Hardened Steel	Steel	3/8-16	3MD70, 5LV12
6894167		2.5" dia. Quick-Change Tip, red, medium	2 1/2	Medium	Vinyl	Red	7/16-14	3MD68, 5LV14, 5LV13
6894169		2.5" dia. Quick-Change Tip, green, tough	2 1/2	Tough	Vinyl	Green	7/16-14	3MD68, 5LV14, 5LV13
6894168		2.5" dia. Quick-Change Tip, cream, medium-hard	2 1/2	Medium-Hard	Nylon	Cream	7/16-14	3MD68, 5LV14, 5LV13
6894166		2.5" dia. Quick-Change Tip, black, hard	2 1/2	Hard	Nylon	Black	7/16-14	3MD68, 5LV14, 5LV13
6894230		3" dia. Quick-Change Tip, red, medium	3	Medium	Vinyl	Red	1/2-13	2UV36, 5LV15, 5LV16
6894231		3" dia. Quick-Change Tip, green, tough	3	Tough	Vinyl	Green	1/2-13	2UV36, 5LV15, 5LV16
6894232		3" dia. Quick-Change Tip, cream, medium-hard	3	Medium-Hard	Nylon	Cream	1/2-13	2UV36, 5LV15, 5LV16
6894233		3" dia. Quick-Change Tip, black, hard	3	Hard	Nylon	Black	1/2-13	2UV36, 5LV15, 5LV16

AVAILABLE THROUGH

GRAINGER
 FOR THE ONES WHO GET IT DONE