



RoofPro™ 445XP

15 GA

TOOL SPECIFICATIONS

Trigger	Contact
Op. Pressure	70-120 psi (4.8 - 8.3 bar)
Air Consumption (60 CPM)	3.86 scfm
Air Inlet	¼" NPT
Weight	5.2 lbs (2.35 kg)
Height	10.9" (276 mm)
Length	10.6" (269 mm)
Width	4.5" (114 mm)
Main body material	Aluminum

FASTENER SPECIFICATIONS



Capacity	120
Range	¾" - 1¾" (19mm - 44mm)
Collation	15° flat wire welded coil
Shank	.120
Series	MO

INCLUDES

- 5 year limited warranty
- Wrenches, tool oil

SOLD SEPARATELY

PARTS KIT

YK0865 Repair kit

VINYL SIDING ATTACHMENT

HA0308 Vinyl siding kit



1¾" Coil Roofing Nailer

ITEM #8V0001N

Lightweight, well-balanced, speedy, easy-to-load and powerful, the RoofPro445XP sets new standards for durability and serviceability. Its innovative feed system reduces air consumption without compromising speed. Its bi-metal driver blade increases longevity. And it's easy to service in the field. Drives fasteners from ¾" to 1¾".

APPLICATIONS

- Asphalt and fiberglass shingle nailing
- Attaching tar paper, metal drip edge and insulation board
- Vinyl and aluminum siding, with an optional attachment (part # HA0308)

FEATURES AND BENEFITS

- Innovative firing valve - reduces air consumption without compromise on power or speed
- Bi-metal driver blade reduces wear and improves durability
- Power in, power out feed system - improves speed and delivers consistent drives
- Metal wear plate in nail canister - reduces canister wear and helps improve nail feed
- Adjustable and removable shingle guide
- Aluminum mainbody and cap
- Weighs just 5.2 lbs. for easy one-handed operation
- Tool-free adjustable depth-of-drive

RoofPro™ 445XP

1¾" Coil Roofing Nailer

ITEM #8V0001N



Easily Served
access to all wear parts
from the top of the tool.

Metal Wear Plate.

Tool-free Adjustable
Depth-of-Drive
allows user to achieve precise
fastener placement.

Metal Wear Plate.

Comfort Grip
Reduces fatigue
Increases productivity.

Innovative Firing Valve
reduces air consumption without
compromise on power or speed.

Canister Adjustment
ensures consistent nail feed
accommodates entire range
of roofing nails.

Canister Metal Wear Plate
reduces wear and helps improve nail feed.

Adjustable & Removable Shingle Guide
for consistent shingle placement.

EZ-load Design
clear magazine door,
easily see when to reload.

Vinyl Siding Attachment for RoofPro445XP
convert your RoofPro445XP to a vinyl siding nailer.
Sold separately: part # HA0308



Choose the right actuation mode

Sequential Actuation (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tool to ensure proper use and safety precautions. For additional information on SENCO fastening systems and how SENCO will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: senco.com