




SC2

TOOL SPECIFICATIONS

Trigger	Sequential
Op. Pressure	80-110 psi (5.5 - 7.5 bar)
Air Consumption (60 CPM)	3.7 scfm
Air Inlet	3/8" NPT
Weight	6.9 lbs (3.1 kg)
Height	9.44" (240 mm)
Length	12.5" (318 mm)
Width	2" (50.8 mm)
Main body material	Aluminum

FASTENER SPECIFICATIONS



Capacity	80
Range	1/4" - 1/2" (7mm - 13mm)
Crown	1"
Collation	Straight glued strip
Series	X

INCLUDES

- 5 year limited warranty

SOLD SEPARATELY

PARTS KIT

YK0371	Repair kit
--------	------------



Sencor® Corrugated Fastener

ITEM #470001N

The powerful corrugated fastener for hard and dense materials. The versatile SC2 clamps material together and drives three sizes of fasteners for stronger joints. Plus, it eliminates gluing, milling, doweling, screwing and clamping. Takes 1" crown, 1/4" to 1/2" fasteners.

APPLICATIONS

- Joint fastening in wood, crate, pallet, truss & box assembly



FEATURES AND BENEFITS

- Powerful for hard and dense material.
- Eliminate gluing, milling, doweling, screwing and clamping
- Added Strength for larger butt joints.
- Eliminate milling, doweling, clamping, screwing and other time-consuming, cost adding operations
- Sencor® corrugated fasteners provide twice the joint strength of ordinary fasteners