



SCP40XP


TOOL SPECIFICATIONS

Trigger	Selectable actuation
Op. Pressure	80-120 psi (5.5 - 8.3 bar)
Air Consumption (60 CPM)	5.2 scfm
Air Inlet	3/8" NPT
Weight	7.1 lbs (3.2 kg)
Height	12.22" (310 mm)
Length	18.2" (462 mm)
Width	4.5" (114.4 mm)
Main Body Material	Aluminum



FASTENER SPECIFICATIONS

W3 Series



Capacity	42
Range	1/2" - 1 1/2" (12mm - 37mm)
Shank	.109" / .118"
Collation	Straight plastic collated strip
Series	W3

INCLUDES

- 5 year limited warranty

SOLD SEPARATELY

NPC035	Magnetic washer nosepiece
SWM125B	Galvanized metal washer

PARTS KIT

YK0444	Firing system kit
YK0445	Piston stop kit

1 1/2" Pneumatic Concrete & Steel Pinner

ITEM #7J0001N

The SCP40XP drives with the power and durability of a high pressure nailer but at a fraction of the cost of a high pressure system. The standard pressure system is easy to use while being much faster and less costly than gas or powder-actuated alternatives. The SCP40XP features a durable aluminum housing, highly efficient motor design, patented drive selector, narrow nosepiece, and quick and easy two-step fastener loading.

APPLICATIONS

- Fastening of drywall track, wood furring, hat channel, ceiling grid to concrete, concrete block and steel

FEATURES AND BENEFITS

- Does not require costly high pressure compressor system - works with conventional air compressors, hoses, and fittings
- 10 times faster than powder actuated systems
- No licensing required to operate
- Operates in extreme temperatures and altitudes
- Operates in contact or sequential

SCP40XP

1½" Pneumatic Concrete & Steel Pinner

ITEM# 7J0001N



Cap Exhaust
directs exhaust downward.

Full Comfort Grip
resilient grip reduces vibration fatigue.

Powerful and Fast
up to 10 times faster than powder
actuated systems.

Standard Air Pressure Pneumatic System
does not require costly high pressure compressor system.

Aluminum Housing
lightweight, superior durability.

Patented Drive Selector
contact or sequential trigger activation.

Hardened Driver Blade
for longer life.


Rear Two-Step Loading
quick and easy for right
or left handers.

Narrow Nose
shoots hat-channel.



Optional Magnetic Washer Nosepiece
holds metal washers.

SOLD SEPARATELY
Magnetic Washer Nosepiece
Item #NPC035
Fastening attachment for
plaster, stucco and
building wrap applications.



Galvanized Metal Washer

ITEM #	Diameter	Box Count	Fits SCP40XP
SWM125B	1¼"	1M	.109" Dia. Concrete Pins

Choose the right actuation mode

Sequential Actuation (also known as restrictive trigger or trigger fire) operates in the following a sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tool to ensure proper use and safety precautions. For additional information on SENCO fastening systems and how SENCO will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: senco.com