



SHF200

16 GA

TOOL SPECIFICATIONS

Trigger	Sequential actuation
Op. Pressure	90-110 psi (6.2 - 7.6 bar)
Air Consumption (60 CPM)	2.52 scfm
Air Inlet	1/4" NPT
Weight	10.1 lbs (4.58 kg)
Height	21.5" (546 mm)
Length	17.8" (452 mm)
Width	3.1" (78 mm)
Main Body Material	Aluminum

FASTENER SPECIFICATIONS

RW Series	1 1/2" - 2"
Capacity	107
Range	1 1/2" - 2" (38mm - 50mm)
Shank	.072
Collation	16 ga. straight glued strip
Series	RW

INCLUDES

- 5 year limited warranty
- Case, mallet, oil, wrenches and 1/4" air fitting



2" Hardwood Flooring Nailer

ITEM# 8D0001N

The SHF200 is a professional-grade pneumatic hardwood flooring cleat nailer. It provides consistent driving power for flush, professional-quality installation. It uses 1 1/2" - 2" L-shaped cleats that hold the wood securely yet allow for seasonal expansion and contraction. The long ergonomically designed handle helps minimize user fatigue.

APPLICATIONS

- Installation of 1/2" and 3/4" thick hardwood and hardwood laminate flooring.

FEATURES AND BENEFITS

- Easy on the arm, it's pneumatic action requires a single strike to drive fastener
- Innovative non-marring base that adjust between 1/2" and 3/4" flooring without the use of tools
- Lightweight and well-balanced, yet 5% more powerful than competitive flooring nailers
- Safety trigger prevents accidental ejection of fasteners
- Extra-long ergonomic handle reduces the amount the operator has to bend over

SHF200

2" Hardwood Flooring Nailer

ITEM# 8D0001N



Pneumatic Driving Action
Consistently drives fastener for easier installation.

Angled Air Fitting
hose does not interfere with magazine or operator.

Hardened Driver Blade
for longer life.

Rear Load Magazine
drives 0.063" L-type cleats in 1-1/2", 1-3/4" and 2" lengths.

Tool-Free Base Adjustment
unique base design allows user to rotate base to desired thickness without additional tools.

Ergonomic Design
longer handle helps minimize user fatigue.

Balance for Stability
tool sits upright for smoother floor installation.

Mallet Actuated
mallet actuated firing simultaneously sets floor boards (tongue and groove) and drives cleat into material groove.

Aluminum Housing
robust housing design.

Includes Non Marring Mallet.



Choose the right actuation mode

Sequential Actuation (also known as restrictive trigger or trigger fire) operates in the following a sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tool to ensure proper use and safety precautions. For additional information on Senco fastening systems and how Senco will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: senco.com