

**SNS41****16_{GA}****17_{GA}**

TOOL SPECIFICATIONS

Trigger	Contact
Op. Pressure	80-120 psi (5.5 - 8.3 bar)
Air Consumption (60 CPM)	5.4 scfm
Air Inlet	3/8" NPT
Weight	4.6 lbs (2.1 kg)
Height	10.75" (273 mm)
Length	15" (381 mm)
Width	3.5" (89 mm)
Main Body Material	Aluminum

FASTENER SPECIFICATIONS

Capacity	160
Collation	Straight glued and taped strip

O		1"-2"
		7/16"
Series	O-wire 17 ga.	
Length	1"-2"	
Crown	7/16"	

N		1"-2"
		7/16"
Series	N-wire 16 ga.	
Length	1"-2"	
Crown	7/16"	

INCLUDES

- 5 year limited warranty

SOLD SEPARATELY

PARTS KIT

YK0423	Repair kit
--------	------------



16-17 Ga. Heavy Wire Staplers

ITEM #3L0003N

For applications where fast, multi-directional stitching is desired, the SNS41 is your stapler. Ideal for ridge beams and all types of sheathing.

Drives 7/16" crown heavy wire staples from 1" to 2".

APPLICATIONS

- Sheathing, subflooring, crate and box assembly, furring, fascia and soffits and ridge beam assembly

FEATURES AND BENEFITS

- Durable construction minimizes downtime and operation costs
- EZ-Clear™ latch virtually eliminates downtime caused by fastener jams
- Fast, multi-directional stitching

SNS41

16-17 Gauge Heavy Wire Staplers

ITEM #3L0003N



360° Rotatable Exhaust
no tool required, quiet design.

Soft Comfort Grip
reduces vibration fatigue, increases productivity.

Aluminum mainbody
weighs just 4.6 lbs. for ease
of use and maneuverability.

Adjustable Depth-of-Drive
drives staples to a consistent and
controllable depth.

EZ-Clear™ Latch
quick and easy clearing of fastener jams.

Multi-Directional Stitching
up 14 staples per second.



Choose the right actuation mode

Sequential Actuation (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tool to ensure proper use and safety precautions. For additional information on SENCO fastening systems and how SENCO will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: senco.com